

[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Parts and ...](#) / [Hydraulic Filter ...](#) / [Replacement Eleme...](#) / 925385

## Replacement Elements - CN Series

Part #: 925385



High efficiency genuine replacement elements for Parker 15/40/80CN Series medium pressure hydraulic filters.

[View Series Page](#)  [Share / Email](#)  [Print](#) 

### Technical Specifications



Division: Hydraulic and Industrial Process Filtration EMEA  
 For Use With: 15CN  
 Length: Length 1  
 Brand: Parker  
 Technology: Filtration  
 Filter Element Type: 10C cellulose  
 Seal Material: Fluoroelastomer  
 Product Type: Hydraulic Oil Filter  
 Micron Rating: 10 µm  
 Filter Type: Medium Pressure Inline Filter  
 Product Series: Replacement Elements - CN Series

Industry:
 

- Industrial Manufacturing Equipment
- Automotive
- Food & Beverage
- Rubber & Plastics
- Metals
- Off-road Machinery
- Agriculture
- Construction
- Forestry
- Lawn & Turf
- Mining
- Materials Handling
- Government
- Military
- Defence
- Power Generation & Renewable Energy
- Transportation
- Rail
- Trucks & Buses

Application:
 

- Compressor Lube Oil
- Off-line Filter Loops
- Machine Tools (Automotive Standard)
- Hydrostatic Drive Charge Pumps
- Mobile Equipment
- Pilot Lines for Servo Controls
- Oil Patch Drilling Equipment
- Injection Molding

For Fluid Type: Suitable for use with mineral and vegetable oils, and some synthetic oils.

Flow Rate: 0 to 600 L/min

Operating Pressure:
 

- Maximum: 70 bar (1015 psi)
- Seal material Nitrile: -40°C to +100°C (-40°F to +212°F)

Operating Temperature:
 

- Seal material Fluoroelastomer: -20°C to +120°C (-4°F to +248°F)
- 40 to +100°C

 [Safety Warning](#)

## Item Information

The 15/40/80CN Series is a range of medium pressure filters offering an economical 'multipurpose' filter solution.



ffered with two types of element:

- The conventional element, making use of the Microglass media and in some sizes also available with ParGelWater removal media.

### Parker Sales Company UK

- The Ecoglass element, an environmentally friendly design without metal inner core. The Eco elements are used in versions of the CN filter with an [www.parker.com](http://www.parker.com) [support.parker@parker.com](mailto:support.parker@parker.com) [+44 \(0\)1926 317878](tel:+441926317878) the bowl of the filter. Having no metal content in the element reduces the overall weight with 50% and makes it possible to dispose of the used element in an environmentally friendly way by incineration, also lowering disposal costs.

These elements are designed with the latest in filter media technology for first class system protection.

### + Company Information

Using genuine Parker replacement elements guarantees Parker's quality of filtration. Using after market filters with unknown media quality may save initial cost, but can increase overall costs by requiring more element change outs and potentially causing system downtime. Protect your investment by always buying genuine Parker replacement elements.

### + Help & Support

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

### + Follow Us :

## CAD Drawings + Files

## Related Documents

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



