



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Parts and ...](#) / [Hydraulic Filter ...](#) / [Switches, Gauges ...](#) / 926748

# Switches, Gauges and Indicators

Part #: 926748



12-35VDC LED Visual DIN 43650 Socket

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Seal Material:	Fluorocarbon	Product Series:	Moduflow Plus ILP, DILP
Signal Output:	Visual 4 Band	Product Type:	Differential Pressure Indicator
Maximum Operating Pressure:	200 psi (13 bar)	Maximum Operating Temperature:	275 F (135 C)
Indicator Pressure Setting:	35 psid (2.4 bar)		

[Safety Warning](#)

## Item Information

Parker's Hydraulic and Fuel Filtration Division offers a broad range of gauges, switches, and indicators across multiple filter product series. Differential pressure increases as a hydraulic filter element captures harmful contamination from system fluid. Filter elements must be replaced once the specified differential pressure is reached. Parker's indicators signal when a filter element must be replaced to ensure system cleanliness and protect system critical assets.

Indicator Types: Pressure Gauge, Vacuum Gauge, Pressure Switch, Visual, Electrical/Visual, Electrical Reed Switch, Analog 4-20mA  
Applicable Filter Series: 12AT, 50AT, 80AT, 80UT, Moduflow Plus ILP DILP, PT, GLF, BGT17, 15P, 30P, 50P, WPF

## CAD Drawings + Files

## Related Documents





**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

---

© PARKER HANNIFIN CORP 2024

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



