

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Parts and ...](#) / [Hydraulic Filter ...](#) / [Replacement Eleme...](#) / 929927Q

# Replacement Elements - CN Series

[Solutions](#)

Part #: 929927Q

[Where to Buy](#)



High efficiency genuine replacement elements for Parker 15/40/80CN Series medium pressure hydraulic filters.

[View Series Page](#) [Share](#) / [Email](#) [Print](#)

## Technical Specifications

For Use With:	80CN
Division:	Hydraulic and Industrial Process Filtration EMEA
Length:	Length 2
Brand:	Parker
Technology:	Filtration
Filter Element Type:	20Q Microglass
Seal Material:	Fluoroelastomer
Product Type:	Hydraulic Oil Filter
Filter Type:	Medium Pressure Inline Filter
Micron Rating:	20µm
Product Series:	Replacement Elements - CN Series
Industry:	<ul style="list-style-type: none"> <li>• Industrial Manufacturing Equipment</li> <li>- Automotive</li> <li>- Food &amp; Beverage</li> <li>- Rubber &amp; Plastics</li> <li>- Metals</li> <li>• Off-road Machinery</li> <li>- Agriculture</li> <li>- Construction</li> <li>- Forestry</li> <li>- Lawn &amp; Turf</li> <li>- Mining</li> <li>- Materials Handling</li> <li>• Government</li> <li>- Military</li> <li>- Defence</li> <li>• Power Generation &amp; Renewable Energy</li> <li>• Transportation</li> <li>- Rail</li> <li>- Trucks &amp; Buses</li> </ul>

### Application:

- Compressor Lube Oil
- Off-line Filter Loops
- Machine Tools (Automotive Standard)
- Hydrostatic Drive Charge Pumps
- Mobile Equipment
- Pilot Lines for Servo Controls
- Oil Patch Drilling Equipment
- Injection Molding

### For Fluid Type:

Suitable for use with mineral and vegetable oils, and some synthetic oils.

### Flow Rate:

0 to 600 L/min

### Operating Pressure:

Maximum:  
70 bar (1015 psi)

### Operating Temperature:

Seal material Nitrile:  
-40°C to +100°C  
(-40°F to +212°F)

Seal material Fluoroelastomer:  
-20°C to +120°C  
(-4°F to +248°F)-40 to +100°C

Safety Warning

## Item Information



The 15/10/00CN Series is a range of medium pressure filters offering an economical 'multipurpose' filter solution.



Our filters can be offered with two types of element:

#### Home

The conventional element, making use of the Microglass media and in some sizes also available with ParGelWater removal media.

#### Products

The Eco element, an environmentally friendly design without metal inner core. The Eco elements are used in versions of the CN filter with an Eco inner core fixed permanently inside the bowl of the filter. Having no metal content in the element reduces the overall weight with 50% and

makes it possible to dispose of the used element in an environmentally friendly way by incineration, also lowering disposal costs.

#### Support

Our elements are designed with the latest in filter media technology for first class system protection.

#### Industries

Genuine Parker replacement elements guarantees Parker's quality of filtration. Using after market filters with unknown media quality may save initial cost, but can increase overall costs by requiring more element change outs and potentially causing system downtime. Protect your investment by always buying genuine Parker replacement elements.

#### Services

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

#### Solutions

---

## CAD Drawings + Files



---

## Related Documents



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)

+44 (0)1926 317878

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

© PARKER HANNIFIN CORP 2024

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---

