= Parker		
<u>Home</u>		
Products		
Support		
Industries		
<u>Services</u>		
Solutions		
Where to Buy		

Home / Products / Filters, Collecto... / Filter Parts and ... / Hydraulic Filter ... / Replacement Eleme... / 932610Q

Replacement Elements - CN Series

Part #: 932610Q



High efficiency genuine replacement elements for Parker 15/40/80CN Series medium pressure hydraulic filters.

Ð

View Series Page 😑 Share / Email 🕐 Print 🖨

Technical Specifications

Octimate Table For Fluid Type: Subtable for Sew With Hindref and Vegetable bils, and some for Use with Hindref and Vegetable bils, and with Hindref and Vegetable bils. For Editable bils, and With Hindref and Vegetable bils, and with Hindref and Vegetable bils. Yee Vegetable bils Advertable bils For Vegetable	Division: For Use With: Length: Brand: Technology: Filter Element Type: Seal Material:	Hydraulic and Industrial Process Filtration EMEA 15CN Length 1 Parker Filtration 02Q Microglass Fluoroelastomer	Application:	 Compressor Lube Oil Off-line Filter Loops Machine Tools (Automotive Standard) Hydrostatic Drive Charge Pumps Mobile Equipment Pilot Lines for Servo Controls Oil Patch Drilling Equipment Injection Molding Suitable for use with mineral and vegetable oils, and
Micron Rating: 2 μm Operating Pressure: Maximum: 70 bar (1015 psi) Seal material Nitrile: -40°C to +100°C -40°C to +100°C (-40°F to +212°F) Product Series: • Industrial Manufacturing Equipment - Automotive - Rubber & Plastics - Rubber & Plastics • Operating Temperature: Maximum: 70 bar (1015 psi) Seal material Nitrile: -40°C to +100°C (-40°F to +212°F) • Off-road Machinery - Rubber & Plastics - Metals • Off-road Machinery - Agriculture - Construction - Forestry - Lawn & Turf • Seal material Fluoroelastomer: - 20°C to +120°C (-4°F to +248°F)-40 to +100°C Industry: • Off-road Machinery - Agriculture - Construction - Forestry - Lawn & Turf • Off-road Machinery - Agriculture - Construction - Forestry - Lawn & Turf Industry: • Off-road Machinery - Materials Handling • Operating Temperature: • Seal material Fluoroelastomer: - 20°C to +120°C (-4°F to +248°F)-40 to +100°C • Off-road Machinery - Agriculture - Construction - Forestry - Lawn & Turf • Operating Temperature: • Seal material Fluoroelastomer: - 20°C to +120°C (-4°F to +248°F)-40 to +100°C • Off-road Machinery - Agriculture • Operating - Operation - Forestry - Lawn & Turf • Operating - Materials Handling • Operation - Power Generation & Renewable Energy • Transportation - Rail	<i><i>³¹</i></i>	2		,
Microfic Rating. 2 µm Operating Pressure: 70 bar (1015 psi) Product Series: Replacement Elements - CN Series Seal material Nitrile: Industrial Manufacturing Equipment -Automotive -40°C to +100°C - Food & Beverage Operating (-40°F to +212°F) - Rubber & Plastics Temperature: Seal material Fluoroelastomer: - Metals - Off-road Machinery - Agriculture - Construction - Construction - Construction - Forestry - Lawn & Turf - Metrials - Metrials - Government - Military - Defence - Power Generation & Renewable Energy - Power Generation & Renewable Energy				
- 110/45 & DUSES	Product Series:	Replacement Elements - CN Series • Industrial Manufacturing Equipment - Automotive • Food & Beverage • Rubber & Plastics • Metals • Off-road Machinery • Agriculture • Construction • Forestry • Lawn & Turf • Mining • Materials Handling • Government • Military • Defence • Power Generation & Renewable Energy • Transportation • Rail	Operating	70 bar (1015 psi) Seal material Nitrile: -40°C to +100°C (-40°F to +212°F) Seal material Fluoroelastomer: -20°C to +120°C
A Safety Warning		- 110003 & 20363		

Item Information

The 15/40/80CN Series is a range of medium pressure filters offering an economical 'multipurpose' filter solution.

ffered with two types of element:

• The conventional element, making use of the Microglass media and in some sizes also available with ParGelWater removal media. Parker Sales Company UK

• The Ecoglass element, an environmentally friendly design without metal inner core. The Eco elements are used in versions of the CN filter with an **Res.uk.vestgerm@auppret.nerkeringme** the bowl of the filter. Having no metal content in the element reduces the overall weight with 50% and **http://www.seconder.nerkeringme** the used element in an environmentally friendly way by incineration, also lowering disposal costs.

These elements are designed with the latest in filter media technology for first class system protection.

+ Company Information

Using genuine Parker replacement elements guarantees Parker's quality of filtration. Using after market filters with unknown media quality may save obtain the perturbation of the perturb

🕇 of Hilb 🗞 Hilb And to not a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

+ Follow Us :		
CAD Drawings + Files		+
	© PARKER HANNIFIN CORP 2024	
Related Documents	ENGINEERING YOUR SUCCESS.	+
	SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS	