

View Series Page Share / Email Print

Technical Specifications

Division:	Hydraulic and Industrial Process Filtration EMEA		
For Use With:	40CN		
Length:	Length 1	Application:	<ul style="list-style-type: none"> • Compressor Lube Oil • Off-line Filter Loops • Machine Tools (Automotive Standard) • Hydrostatic Drive Charge Pumps • Mobile Equipment • Pilot Lines for Servo Controls • Oil Patch Drilling Equipment • Injection Molding
Brand:	Parker		
Technology:	Filtration		
Filter Element Type:	05QE Ecoglass	For Fluid Type:	Suitable for use with mineral and vegetable oils, and some synthetic oils.
Seal Material:	Fluoroelastomer	Flow Rate:	0 to 600 L/min
Product Type:	Hydraulic Oil Filter	Operating Pressure:	Maximum: 70 bar (1015 psi) Seal material Nitrile: -40°C to +100°C (-40°F to +212°F)
Filter Type:	Medium Pressure Inline Filter	Operating Temperature:	Seal material Fluoroelastomer: -20°C to +120°C (-4°F to +248°F)-40 to +100°C
Micron Rating:	5 µm		
Product Series:	Replacement Elements - CN Series <ul style="list-style-type: none"> • Industrial Manufacturing Equipment - Automotive - Food & Beverage - Rubber & Plastics - Metals 		
	<ul style="list-style-type: none"> • Off-road Machinery - Agriculture - Construction - Forestry - Lawn & Turf - Mining - Materials Handling 		
Industry:	<ul style="list-style-type: none"> • Government - Military - Defence 		
	<ul style="list-style-type: none"> • Power Generation & Renewable Energy 		
	<ul style="list-style-type: none"> • Transportation - Rail - Trucks & Buses 		



Item Information



The 15/10/00CN Series is a range of medium pressure filters offering an economical 'multipurpose' filter solution.



Our filters are offered with two types of element:

Home

The conventional element, making use of the Microglass media and in some sizes also available with ParGelWater removal media.

Products

The Ecoglass element, an environmentally friendly design without metal inner core. The Eco elements are used in versions of the CN filter with an Eco inner core fixed permanently inside the bowl of the filter. Having no metal content in the element reduces the overall weight with 50% and

makes it possible to dispose of the used element in an environmentally friendly way by incineration, also lowering disposal costs.

Support

Industries

Our elements are designed with the latest in filter media technology for first class system protection.

Services

Genuine Parker replacement elements guarantees Parker's quality of filtration. Using after market filters with unknown media quality may save initial cost, but can increase overall costs by requiring more element change outs and potentially causing system downtime. Protect your

investment by always buying genuine Parker replacement elements.

Solutions

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com

+44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

