

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Replacement Engin...](#) / [Hydraulic Filter ...](#) / [Replacement Eleme...](#) / 938781Q


[Services](#)

# Replacement Elements - High Pressure In-Line Filter 70/70 Eco Series

[Solutions](#)

Part #: 938781Q

[Where to Buy](#)



High pressure inline hydraulic oil filter series is a proven filter concept, up to 500l/min and pressures up to 420 bar.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

## Technical Specifications

<p>Division: Hydraulic and Industrial Process Filtration EMEA</p> <p>For Use With: 70 series length 3</p> <p>Filter Element Type: 10Q Microglass</p> <p>Brand: Parker</p> <p>Micron Rating: 10 µm</p> <p>Technology: Filtration</p> <p>Seal Material: Nitrile</p> <p>Product Type: Hydraulic Oil Filter Replacement Elements</p> <p>Product Series: 70/70 Eco Series</p> <p>Length: 328 mm</p> <p>End Cap Material: Plastic</p> <p>Industry: Mining Material handling Construction Marine Power Generation Industrial Machinery Injection Moulding</p>	<p>Application:</p> <p>Drilling machines Dumpers Hydraulic power units Mobile cranes Reach stackers Container handling equipment Cranes Excavators Crushing machines Propulsion systems Deck machinery Wind turbines Hydropower Servo controls</p> <p>Options: None</p> <p>For Fluid Type: Suitable for use with mineral and vegetable oils, and some synthetic oils.</p> <p>Operating Pressure: 420 bar (350 bar Length 4) Maximum.</p> <p>Operating Temperature: -40°C to +100°C.</p>
--	---

[Safety Warning](#)

## Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.



For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

**Industries**

**CAD Drawings + Files**



**Solutions**

**Related Documents**



**Where to Buy**



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---

