

Duplex Hydraulic Filter Replacement Elements - DF25 Series

Part #: 939130



Parker DF Series Replacement Elements are designed for use with DF Duplex Series Hydraulic Filters. Filters for fuel, lube and hydraulic systems, maximum flow rate 100l/min (6m³/h).

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Filter Element Type:	15N Cellulose	Length:	253 mm
Micron Rating:	15 µm	Compatible Series:	DF25 Series Duplex Filter
Seal Material:	Fluoroelastomer		

[Safety Warning](#)

Item Information

The DF25 is a duplex filter suitable for continuous operation. Both the selecting valve end positions are secured with a locking mechanism. Sturdy cast iron housing with a pressure rating of 40 bar. The DF25 has drain plugs at the bottom and air vent plugs at the top. Element change from the top provides for a clean and tidy service. There is an integrated connection for a differential pressure indicator. The filter has threaded connection ports and the flange can also be used for side-block mounting. Behind the flange there are plugged alternative connection ports: The IN-port on the left side and the OUT-port at the top.

Applications:

- Diesel engine fuel systems
- Industrial lube oil systems
- Industrial medium pressure hydraulic systems

CAD Drawings + Files



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

