



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)


[Solutions](#)

[Where to Buy](#)

[Home](#) / [Products](#) / [Filters, Collectors](#) / [Replacement Filter Elements](#) / [Lubrication Oil Filters](#) / [Replacement Elements](#) / 939196

Replacement Elements - GS Series

Part #: 939196



The replacement elements of the Parker GS Filter Series feature high quality glass fibre and metal mesh filter materials.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

For Use With:	GS7	Diameter:	106 mm
Filter Element Type:	500W Wiremesh	Seal Material:	Fluoroelastomer
Micron Rating:	500 µm	Options:	Standard
Length:	259 mm		

[Safety Warning](#)

Item Information

The high quality replacement elements of the GS filter series are available in a wide variety of sizes and with several filter materials and micron ratings. These replacement elements ensure the quality of filtration Parker is known for.

Fluid passes through the elements in an inside-to-outside direction, collecting particles inside the filter cartridge. This eliminates re-injection of contaminant during element change. Clean fluid then returns to the reservoir.

The GS series filters are available with Magnetic pre-filtration. The magnet column removes ferrous particles, even during times of bypass, and extends the life of the filter element.

Using genuine Parker replacement elements guarantees Parker's quality of filtration. Using after market filters with unknown media quality may save initial cost, but can increase overall costs by requiring more element change outs and potentially causing system downtime. Protect your investment by always buying genuine Parker replacement elements.



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

