

Replacement Elements - SF1040 Series

Part #: 939382Q



Replacement elements for Parker SF1040 low pressure, high flow, inline filters for hydraulic systems.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|--------------------------------|------------------|----------------------|---------------------------------|
| Micron Rating: | 10 µm | Filter Element Type: | Conventional disposable element |
| Filter Material: | 10Q Microglass | Length: | 303 mm |
| Product Series: | SF1040 | Diameter: | 271 mm |
| Seal Material: | Nitrile | Options: | Standard |
| Maximum Pressure Differential: | 5 bar (ISO 2941) | | |

[Safety Warning](#)

Item Information

The high quality replacement elements for the SF1040 filter series are available with several filter materials and micron ratings.

These genuine Parker replacement elements ensure the high quality of filtration Parker is known for.

SF1040 filter use 2 primary elements, an option is available with a (one) secondary safety filter element inside the 2 primary filter elements, to secure a certain degree of filtration even in a bypass situations.

The SF1040 elements are also used in the SFR1040 and SFH1040 filter models.

Using genuine Parker replacement elements guarantees Parker's quality of filtration. Using after market filters with unknown media quality may save initial cost, but can increase overall costs by requiring more element change outs and potentially causing system downtime. Protect your investment by always buying genuine Parker replacement elements.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

