

### <u>Home</u>

Products

Support

Industries oducts / Filters, Collecto... / Replacement Engin... / Hydraulic Filter ... / Tank Top Return L... / 944859Q

# <sup>s</sup>Tänk Top Return Line Hydraulic Filter Replacement Elements – শশিল্টtect® GLF Series

Where to Buy Part #: 944859Q



Parker GLF Series Replacement Elements are designed for use with GLF Series Tank Top Return Line Hydraulic Filters. The elements combine high efficiency filtration with low cost installation and are available with ratings ranging from 2 - 20 microns.

Ð

View Series Page ☷	View Catalog(s) 🗹
Share / Email 🔿	Print 🖶

# **Technical Specifications**

Length: Division: Brand: For Use With: Technology: Bypass Valve Pressure Rating: Product Type: Seal Material:	Length 1 Hydraulic and Industrial Process Filtration EMEA Parker GLF size 4 Filtration 1.7 bar Hydraulic Oil Filter Nitrile	Application:	<ul> <li>Deck and mobile cranes</li> <li>Firefighting equipment</li> <li>Forwarders</li> <li>Hydraulic presses</li> <li>Marine steering units</li> <li>Power packs</li> <li>Waste management, dump and fork lift trucks</li> <li>Excavators</li> <li>Harvesters</li> <li>Waste balers</li> <li>Dump trucks &amp; drilling machines for mining</li> </ul>
Filter Type:	Tanktop Return Line	For Fluid Type:	Hydraulic Oil 10 bar
Micron Rating:	5 µm	Operating Pressure:	150 psi
Product Series:	iProtect® GLF Series Replacement Elements <ul> <li>Agriculture</li> </ul>	Operating Temperature:	-40 to +212°F -40 to +100°C
	Construction     Oil and Gas     Marine	Flow Rate:	0 to 1700 L/min
		Filter Element Type:	Quantumfiber™
	• Forestry	Specifications Met:	Degree of filtration determined by multipass test according to ISO 16889.
A Safety Warning			

A Safety Warning

# **Item Information**

ation —

Parker GLF Series Low Pressure Return Line Hydraulic Filters combine high efficiency microglass filtration with low cost installation in a new patented element design. The filter element assembly is designed for direct mounting and can be easily removed for maintenance, providing customers with both convenience and dependability.

🛺 arker GLF Series Replacement Elements ensures protection against contaminant ingress in hydraulic circuits, which 🗰 erw 🎎 can entical system components, such as pumps, valves and cylinders, resulting in increased downtime and higher operational costs. The Helements are available in single and double lengths and several micron ratings (2, 5, 10, and 20) to meet the individual requirements of customers' applications.

Products GLF Series Low Pressure Return Line Filters provide an economical alternative for quality tank top-mounted filtration. The filter is ideally suited for use with equipment that is required to operate in harsh environments, including mining, construction, marine, forestry, and agricultural operations.

Industries mineral oils H to class HLPD (DIN51524)

• Operating fluids DIN ISO 2943 Services tion fluids ISO6743, APJ, DIN 51517, ACEA, ASTM

Vegetable oils

SolutionsVater glycols

· On request - Industrial grade phosphate esters

Whene to Buy sive synthetic oils

Non aggressive bio degradable oils (HETC, HEPC and HEES to VDMA 24568)

Benefits:

Prevents contamination and ingress of dirt, sand, dust, metal, etc. into hydraulic system.

• Reduces component failures in between service intervals, increasing machine availability and reducing the cost of ownership over the life of your machine

Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life.

· Microglass media maximizes filtration capacity and element life, while maintaining low pressure drop, even under cold start conditions. · Element assembly is designed for direct mounting and easy removal for maintenance, providing customers with both convenience and

dependability.

Features:

• High efficiency Quantµmfiber™ media increases particle capture and dirt holding capacity.

• Flow rate up to 3200 L/min (845 GPM).

• Pressure rating - up to 10.3 bar (150 psi) static.

· Single or double length configurations available.

- · OEM lock available for use with genuine filter products.
- · Several ratings available, including 2, 5, 10, and 20 micron.

· Customer branding possible.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

### CAD Drawings + Files

# Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS



### <u>Home</u>

Products

Support

Industries

Services

Solutions

Where to Buy