

<u>Home</u>

Products

Support

Industriesoducts / Filters, Collecto... / Filter Parts and ... / Hydraulic Filter ... / Hydraulic Reservo... / ABL1U112QXWL3V

#### Services Hydraulic Reservoir Breather / Air Filter – ABL Series Solutions

### <u>wRardt#вA</u>BL1U112QXWL3V



The Parker ABL Series is an eco-friendly reservoir breather / air filter designed to protect hydraulic systems from contaminant ingress. The breather utilizes replaceable LEIF® filter elements and is capable of airflows up to 2000 L/min (528 GPM).

 $\oplus$ 

 View Series Page ⋮
 View Catalog(s) 

 Share / Email 
 Print 号

### **Technical Specifications**

Filter Material: Outside Diameter: Seal Material: Flow Rate: Housing Material: A Safety Warning 3 micron abs. for air 127 mm Silicon (integrated in LEIF element) 1000 L/min High impact strength composite Operating Temperature: Connection: Flow Capacity (I/min): Indicator Type: Options: -20 / +80 °C 11/2 UN-16-2B 1000 \* Visual \* None \*

## **Item Information**

The ABL Series is an environmentally friendly reservoir breather / air filter that features replaceable LEIF® filter elements and silicon end caps. Utilizing high-efficiency glass fiber media (3 micron absolute for air), the breather serves as a critical line of protection against contaminant ingress in hydraulic systems, which can cause costly issues, such as increased wear on pumps and cylinders, decreased performance, and shorter maintenance intervals. Typical applications for the ABL Series breather / air filter include saw mills, agricultural machines, articulated dump trucks, forestry equipment, wheeled loaders, lubricated systems, excavators, industrial power units, and mobile cranes.

The ABL Series is tank-top mounted and features a high impact strength composite housing. It is available in two sizes: the ABL1 for airflows up to 1000 L/min (264 GPM) and the ABL2 for airflows up to 2000 L/min (528 GPM). Multiple connection, indicator, and adapter options are also available to meet the unique requirements of customers' hydraulic systems.

Parker also offers the eco-friendly EAB Series breather / air filter , which offers multiple filtration media options and is designed for airflows up to 1500 L/min (396 GPM).

Markets:

- Agriculture
- Construction
- Oil and Gas
- Marine



# Applications: Home Deck and mobile cranes

- Firefighting equipment Preducts
- Hydraulic presses
- Supporte steering units
- Power packs Industries anagement, dump and fork lift trucks
- Excavators

Selrivices ters

- Waste balers
- Softetions tackers
- Wheeled loaders
- Wheileng Buypment

Industrial power units

Benefits:

- · Prevents contamination and ingress of dirt, sand, dust, metal, etc. into hydraulic circuits
- · Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life
- The use of eco-friendly replaceable elements reduces waste by up to 50% when compared to conventional filters with non-elements

Features:

- · Capable of air flows up to 2000 L/min (528 GPM)
- Operating temperature range: -20 to +80°C (-4 to +175°F)
- Outside diameter: 127mm
- Optional G11/4 adapter or G11/2 adaptor with filler connection
- Connections: threads G11/4, 11/2" UN-16-2B
- · Elements can be used for hydraulic fluids and HEES type fluids only

## **CAD Drawings + Files**

### **Related Documents**

### **Related Products**





Parker Sales Company UK

### psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :



<u>Home</u>

Products

Support

Industries

Services

Solutions

Where to Buy

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS. SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS