


Tank Mounted Suction Filter - ATZ Series

Part #: ATZ2XXXBPXL481



ATZ Series Suction Filters.
Submersible (under oil level) tank-wall mounted suction line filters containing a valve that closes automatically before changing the element.
Maximum flow 300 l/min.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 280 l/min	Options:	2½"SAE with blind flange
Connection Type:	2½"SAE (code 61) + 2 x SAE-16	Indicator Type:	No indicator, port plugged
Filter Element Type:	No element	Seal Material:	Nitrile
Micron Rating:	No element		

[Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The ATZ Series is a compact and robust cast aluminium tank-wall mounted filter, located below tank oil level. This submersible suction line filter offers maximum protection for the hydraulic system pump. When removing the element, the check valve closes automatically, eliminating any chance of oil leakage. Pre-filtration takes place by means of a magnetic column. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. Suitable for heavy duty industrial applications and recommended for reservoirs with high contamination ingress. ATZ Filters are capable of handling nominal flow rates up to 300 l/min.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

