

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Parts and ...](#) / [Hydraulic Filter ...](#) / [Top-mounted Breat...](#) / [B.34.214](#)

[Services](#)

Top-mounted Breathers and Filler Breathers - AB Series

[Solutions](#)

[Part # B.34.214](#)



The Parker AB Series comprises a broad range of top-mounted breathers and filler breathers. The filler breathers protect hydraulic systems from airborne particle ingress, while allowing sufficient airflow into and out of the fluid reservoir.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Technical Specifications

Features:	With locking lug	Technology:	Filtration, Hydraulics
Brand:	Parker	Installation:	Tank hole mounted
Product Type:	Filler Breather Cap	Product Series:	AB Series
Housing Material:	Plated Mild Steel	Connection Type:	6 Hole Installation
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Strainer Type:	95 mm strainer
Pressure Relief Valve Type:	Un-Pressurised	For Fluid Type:	Air
Industry:	Agriculture, Construction, Oil and Gas, Marine, Mining, Forestry	Operating Temperature:	-30 / +90
Flow Rate:	0 l/min	Includes:	With locking lug
Application:	Deck and Mobile Cranes, Firefighting Equipment, Forwarders, Hydraulic Presses, Marine Steering Units, Power Packs, Waste Management, Dump and Fork Lift Trucks, Excavators, Harvesters, Waste Balers, Reach Stackers, Wheeled Loaders, Drilling Equipment, Industrial Power Units	Outside Diameter:	76 mm
Micron Rating:	No element	Mounting Type:	Tanktop
		Seal Material:	No seal
		Filter Material:	No filter element

[Safety Warning](#)

Item Information

Ingress of airborne contaminants into hydraulic systems can cause a number of costly issues, including increased wear on pumps and cylinders, decreased performance, shorter maintenance intervals, and added downtime.

The Parker AB Series comprises a full range of top-mounted breathers and filler breathers designed to prevent this by keeping out harmful contaminants and allowing the tank / fluid reservoir to effectively breath during equipment operation.

Multiple configurations are available to meet the unique requirements of customers' hydraulic systems, including:



EAB Series - Glass-filled nylon or plated metal steel. Multiple installation available including single hole, three hole, or six hole installation. Flow rates up to 620 L/min (163 GMP).

Home

Screw-on type Breathers - Glass-filled nylon or plated metal steel. Multiple connection types available. Flow rates up to 620 L/min (163 GPM). Disticks available with all options (two lengths and in packs of 10).

Products

Lockable

Fillers and Filler Breathers (metal) - Pressurized and unpressurized threaded types available. For added reservoir security and oil protection, certain metal filler breathers can be specified with a locking lug option.

Support

Industries

EAB Series breathers and filler breathers are ideally suited for equipment required to operate in environments laden with dirt and dust.

Services

Prevents contamination and ingress of dirt, sand, dust, metal, etc. into hydraulic circuits, while allowing sufficient airflow into and out of the fluid

Solutions

Where to Buy

Time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life

Features:

- Molded in non-corrodible, glass-filled nylon – strong and light
- Filler breathers available with single hole, six hole, and three hole installation
- Screw-on breather range – G1/2 and G3/4 options
- Compact range – G1/4, G3/8, R1/2 and R3/4 options
- Metal filler breathers – pressurized and unpressurized threaded type
- Flange mounting type options
- Lockable options for reservoir security and oil protection

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Related Products

Hydraulic Reservoir
Breather / Air Filter -
EAB Series



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
