=Parker			
<u>Home</u>			
Products			
<u>Support</u>			
Industries			
<u>Services</u>			
Solutions			
<u>Where to Buy</u>			

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / Tanktop Mounted R... / BGT1105QLVS1ER323

Tanktop Mounted Return Line Filter - BGT Series

Part #: BGT1105QLVS1ER323





The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

View Series Page \Xi Share / Email 📌 Print 🖶

Technical Specifications

Flow Rate:	0 to 480 l/min	Product Series:	BGT Series	
Division:	Hydraulic and Industrial Process Filtration EMEA	Options:	Diffuser type T	
Bypass Valve Pressure Rating:	1.5 bar		 Mobile cranes Excavators Deck cranes Fire fighting equipment Hydraulic presses 	
Brand:	Parker	Application:		
Technology:	Filtration	1		
Connection Type:	2"SAE	Seal Material: Mounting Type: Pressure Rating: Housing Material:	 Industrial power units Fork lift trucks Fluorelastomer Tank Mounted 0-34 bar (0-500 psi) Aluminium 	
Filter Element Type:	05QL Ecoglass			
Product Type:	Hydraulic Filter 5 μm Tanktop Mounted Return Line Filter			
Micron Rating:				
Filter Type:				
Indicator Type:	Electrical 42V, NO/NC, M10x1			
Safety Warning				

Item Information

BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of handling flow rates up to 2400 I/min. They can operate with a maximum working pressure of 10 bar. LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

Product Features:

- BGT features pre-filtration by means of a magnet column.
- · Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.
- Maximum pressure 10 bar. Maximum flow 2400 l/min.
- Patented LEIF® elements safeguard filtration quality.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

+

╇

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS