

# Tanktop Mounted Return Line Filter - BGT Series

Part #: BGT1110QLBG1ER323



The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Filter Element:	10QL Ecoglass *	Filter Type:	Tanktop Mounted Return Line Filter
Flow Capacity (l/min):	390	Product Series:	BGT Series
Bypass Valve (bar):	1,5 *	Indicator Type:	Visual M10x1
Port Connection Type:	2"SAE *	Options:	Diffuser type T
Flow Rate:	0 to 550 l/min		<ul style="list-style-type: none"> <li>• Mobile cranes</li> <li>• Excavators</li> <li>• Deck cranes</li> <li>• Fire fighting equipment</li> <li>• Hydraulic presses</li> <li>• Waste balers</li> <li>• Industrial power units</li> <li>• Fork lift trucks</li> </ul>
Division:	Hydraulic and Industrial Process Filtration EMEA	Application:	
Bypass Valve Pressure Rating:	1.5 bar	Seal Material:	Nitrile
Brand:	Parker	Mounting Type:	Tank Mounted
Technology:	Filtration	Pressure Rating:	0-34 bar (0-500 psi)
Connection Type:	2"SAE	Housing Material:	Aluminium
Filter Element Type:	10QL Ecoglass		
Product Type:	Hydraulic Filter		
Micron Rating:	10 µm		

[Safety Warning](#)

## Item Information

BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of handling



flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.

LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

Product Features:

- BGT features pre-filtration by means of a magnet column.
- Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.
- Maximum pressure 10 bar. Maximum flow 2400 l/min.
- Patented LEIF® elements safeguard filtration quality.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

---

## CAD Drawings + Files



---

## Related Documents



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

---

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



