

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Tanktop Mounted R...](#) / [BGT1110QLBPER323](#)

[Services](#)

Tanktop Mounted Return Line Filter - BGT Series

[Solutions](#)

Part # **BGT1110QLBPER323**



The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Filter Element:	10QL Ecoglass *	Filter Type:	Tanktop Mounted Return Line Filter
Flow Capacity (l/min):	390	Indicator Type:	No indicator, Port plugged R
Bypass Valve (bar):	1,5 *	Product Series:	BGT Series
Port Connection Type:	2"SAE *	Options:	Diffuser type T
Flow Rate:	0 to 550 l/min		• Mobile cranes
Division:	Hydraulic and Industrial Process Filtration	Application:	• Excavators
	EMEA		• Deck cranes
Bypass Valve Pressure Rating:	1.5 bar		• Fire fighting equipment
Brand:	Parker		• Hydraulic presses
Technology:	Filtration	Mounting Type:	• Waste balers
Connection Type:	2"SAE		• Industrial power units
Filter Element Type:	10QL Ecoglass	Seal Material:	• Fork lift trucks
Product Type:	Hydraulic Filter	Pressure Rating:	Tank Mounted
Micron Rating:	10 µm	Housing Material:	Nitrile
			0-34 bar (0-500 psi)
			Aluminium

[Safety Warning](#)

Item Information

BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of handling flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.


LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

Product Features:

- BGT features pre-filtration by means of a magnet column.
- Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.



Maximum pressure 10 bar. Maximum flow 2400 l/min.
Parker elements safeguard filtration quality.



For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Support

Related Documents



Services

Solutions

Where to Buy

Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44201926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

