

Tanktop Mounted Return Line Filter - BGT Series

Part #: BGT11B10QBP2HR32A



The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|-------------------------------|---|-------------------|--|
| Flow Rate: | 0 to 450 l/min | Indicator Type: | No indicator, Port plugged R |
| Division: | Hydraulic and Industrial Process Filtration EMEA | Application: | <ul style="list-style-type: none"> • Mobile cranes • Excavators • Deck cranes • Fire fighting equipment • Hydraulic presses • Waste balers • Industrial power units • Fork lift trucks |
| Bypass Valve Pressure Rating: | 2.0 bar | Options: | Diffuser type T, no magnets |
| Brand: | Parker | Mounting Type: | Tank Mounted |
| Technology: | Filtration | Seal Material: | Nitrile |
| Connection Type: | 2"SAE | Pressure Rating: | 0-34 bar (0-500 psi) |
| Filter Element Type: | 10Q Microglass | Housing Material: | Aluminium |
| Product Type: | Hydraulic Filter | | |
| Micron Rating: | 10 µm | | |
| Filter Type: | Tanktop Mounted Return Line Filter | | |
| Product Series: | BGT Series | | |

[Safety Warning](#)

Item Information

BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.



LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

Product Features:

- BGT features pre-filtration by means of a magnet column.
- Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.
- Maximum pressure 10 bar. Maximum flow 2400 l/min.
- Patented LEIF® elements safeguard filtration quality.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



