=Parker			
<u>Home</u>			
Products			
<u>Support</u>			
Industries			
<u>Services</u>			
Solutions			
<u>Where to Buy</u>			

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / Tanktop Mounted R... / BGT1210QBP2ER32A

Tanktop Mounted Return Line Filter - BGT Series

Part #: BGT1210QBP2ER32A





The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

View Series Page 😑 Share / Email 📌 Print 🖶

Technical Specifications

Division: Flow Rate: Bypass Valve Pressure Rating: Brand: Technology: Connection Type: Product Type: Filter Element Type: Micron Rating: Filter Type: Product Series: Safety Warning

EMEA 0 to 580 l/min 1.5 bar Parker Filtration 2"SAE Hydraulic Filter 10Q Microglass 10 μm Tanktop Mounted Return Line Filter BGT Series

Hydraulic and Industrial Process Filtration

Indicator Type: Options:

Application:

Seal Material: Mounting Type: Pressure Rating: Housing Material: No indicator, Port plugged R Diffuser type T, no magnets

- Mobile cranes
- Excavators
 Deck cranes
- Fire fighting equipment
- Hydraulic presses
- Waste balers
- Industrial power unitsFork lift trucks

ng

Nitrile

Tank Mounted 0-34 bar (0-500 psi) Aluminium

Item Information

BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hyster Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable flow rates up to 2400 I/min. They can operate with a maximum working pressure of 10 bar.

LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

Product Features:

- BGT features pre-filtration by means of a magnet column.
- · Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.
- Maximum pressure 10 bar. Maximum flow 2400 l/min.
- Patented LEIF® elements safeguard filtration quality.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

+

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

 \bigcirc