

Tanktop Mounted Return Line Filter - BGT Series

Part #: BGT1210QLBG1ER323



The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Filter Element:	10QL Ecoglass *	Micron Rating:	10 µm
Bypass Valve (bar):	1,5 *	Filter Type:	Tanktop Mounted Return Line Filter
Flow Capacity (l/min):	500 *	Indicator Type:	Visual M10x1
Port Connection Type:	2"SAE *	Product Series:	BGT Series
Flow Rate:	0 to 580 l/min	Options:	Diffuser type T
Mounting Type:	Tank Mounted, Tank Mounted	Flow Rate:	500 L/min
Division:	Hydraulic and Industrial Process Filtration EMEA	Application:	<ul style="list-style-type: none"> • Mobile cranes • Excavators • Deck cranes • Fire fighting equipment • Hydraulic presses • Waste balers • Industrial power units • Fork lift trucks
Bypass Valve Pressure Rating:	1.5 bar	Seal Material:	Nitrile
Pressure Rating:	10 bar, 0-34 bar (0-500 psi)	Housing Material:	Aluminium, Aluminium
Brand:	Parker	Operating Temperature:	-40 / +100 °C
Technology:	Filtration		
Connection Type:	2"SAE		
Filter Element Type:	10QL Ecoglass		
Product Type:	Hydraulic Filter		

[Safety Warning](#)

Item Information



BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of handling flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.

LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

Product Features:

- BGT features pre-filtration by means of a magnet column.
- Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.
- Maximum pressure 10 bar. Maximum flow 2400 l/min.
- Patented LEIF® elements safeguard filtration quality.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com

+44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



