=Parker			
<u>Home</u>			
Products			
<u>Support</u>			
Industries			
<u>Services</u>			
Solutions			
<u>Where to Buy</u>			

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / Tanktop Mounted R... / BGT1310QBG1ER483

Tanktop Mounted Return Line Filter - BGT Series

Part #: BGT1310QBG1ER483





The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

Ð

View Series Page 🚍 Share / Email 📌 Print 🖶

Technical Specifications

Flow Capacity (l/min):	600	Filter Type:	
Port Connection Type:	3"SAE *	Indicator Type:	
Filter Element:	10Q Microglass *	Product Series:	
Bypass Valve (bar):	1,5 *	Options:	
Flow Rate:	0 to 780 l/min		
Division:	Hydraulic and Industrial Process Filtration EMEA		
Brand:	Parker	Application:	
Bypass Valve Pressure Rating:	1.5 bar		
Technology:	Filtration		
Connection Type:	3"SAE	Seal Material: Mounting Type: Pressure Rating: Housing Material:	
Product Type:	Hydraulic Filter		
Filter Element Type:	10Q Microglass		
Micron Rating:	10 µm		

A Safety Warning

Item Information

BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of handling

Material:

Tanktop Mounted Return Line Filter

Visual M10x1 **BGT Series**

Diffuser type T Mobile cranes Excavators Deck cranes Fire fighting equipment
Hydraulic presses

 Waste balers Industrial power units Fork lift trucks

0-34 bar (0-500 psi) Aluminium

Nitrile Tank Mounted flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.

LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

Product Features:

- BGT features pre-filtration by means of a magnet column.
- Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.
- Maximum pressure 10 bar. Maximum flow 2400 l/min.
- Patented LEIF® elements safeguard filtration quality.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents

+ +



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS