

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Tanktop Mounted R...](#) / [BGT1510QLBG1ER483](#)

[Services](#)

Tanktop Mounted Return Line Filter - BGT Series

[Solutions](#)

Part # **BGT1510QLBG1ER483**



The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Port Connection Type:	3"SAE *	Filter Type:	Tanktop Mounted Return Line Filter
Filter Element:	10QL Ecoglass *	Indicator Type:	Visual M10x1
Bypass Valve (bar):	1,5 *	Product Series:	BGT Series
Flow Capacity (l/min):	1000 *	Application:	<ul style="list-style-type: none"> • Mobile cranes • Excavators • Deck cranes • Fire fighting equipment • Hydraulic presses • Waste balers • Industrial power units • Fork lift trucks
Flow Rate:	0 to 1150 l/min	Options:	Diffuser type T
Division:	Hydraulic and Industrial Process Filtration EMEA	Mounting Type:	Tank Mounted
Bypass Valve Pressure Rating:	1.5 bar	Seal Material:	Nitrile
Brand:	Parker	Pressure Rating:	0-34 bar (0-500 psi)
Technology:	Filtration	Housing Material:	Aluminium
Connection Type:	3"SAE		
Filter Element Type:	10QL Ecoglass		
Product Type:	Hydraulic Filter		
Micron Rating:	10 µm		

[Safety Warning](#)

Item Information


BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of handling flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.

LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

Product Features:

- BGT features pre-filtration by means of a magnet column.
- Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.

Maximum pressure 10 bar. Maximum flow 2400 l/min.
Parker elements safeguard filtration quality.



For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



[Support](#)

Related Documents



[Services](#)

[Solutions](#)

[Where to Buy](#)

Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ [Company Information](#)

+ [Global Operations](#)

+ [Help & Support](#)

+ [Follow Us :](#)

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
