

**Home** 

**Products** 

Support

**Industries** 

**Services** 

**Solutions** 

Where to Buy

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / Tanktop Mounted R... / BGT1602QLBS1ER483

## **Tanktop Mounted Return Line Filter - BGT Series**

Part #: BGT1602QLBS1ER483





The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

View Series Page 

Share / Email 

Print 

Pr

#### **Technical Specifications**

Flow Rate: 0 to 650 I/min

Division: Hydraulic and Industrial Process Filtration EMEA

Bypass Valve Pressure
1.5 bar

Rating:
Brand:
Parker
Technology:
Connection Type:
3"SAE

Filter Element Type: 02QL Ecoglass
Product Type: Hydraulic Filter

Filter Type: Tanktop Mounted Return Line Filter

Micron Rating: 2 μn

Indicator Type: Electrical 42V, NO/NC, M10x1

Safety Warning

Product Series: BGT Series
Options: Diffuser typ

IONS:

• Mobile cranes
• Excavators
• Deck cranes

Application:

• Fire fighting equipment
• Hydraulic presses
• Waste balers
• Industrial power units

· Industrial power units
· Fork lift trucks

Mounting Type: Tank Mounted

Seal Material: Nitrile

Pressure Rating: 0-34 bar (0-500 psi)

Housing Material: Aluminium

### Item Information

BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of handling flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.

LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

#### **Product Features:**

- BGT features pre-filtration by means of a magnet column.
- Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.
- Maximum pressure 10 bar. Maximum flow 2400 l/min.
- Patented LEIF® elements safeguard filtration quality.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

# CAD Drawings + Files + Related Documents +



**Parker Sales Company UK** 

# $\frac{psc.uk.webform@support.parker.com}{+44~(0)1926~317878}$

+ Company Information
+ Global Operations
+ Help & Support
+ Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS