

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collectors](#) / [Filter Assemblies](#) / [Hydraulic Filters](#) / [Tanktop Mounted Return Line Filters](#) / [BGT1710QBPER481](#)

[Services](#)

[Solutions](#)

Tanktop Mounted Return Line Filter - BGT Series

Part # BGT1710QBPER481



The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

[View Series Page](#)
[Share / Email](#)
[Print](#)

Technical Specifications

Flow Rate:	0 to 2000 l/min	Indicator Type:	No indicator, Port plugged R
Division:	Hydraulic and Industrial Process Filtration EMEA		<ul style="list-style-type: none"> • Mobile cranes • Excavators • Deck cranes • Fire fighting equipment • Hydraulic presses • Waste balers • Industrial power units • Fork lift trucks
Bypass Valve Pressure Rating:	1.5 bar	Application:	
Brand:	Parker		
Technology:	Filtration	Options:	No Diffuser
Connection Type:	3"SAE	Mounting Type:	Tank Mounted
Product Type:	Hydraulic Filter	Seal Material:	Nitrile
Filter Element Type:	10Q Microglass	Pressure Rating:	0-34 bar (0-500 psi)
Micron Rating:	10 µm	Housing Material:	Aluminium
Filter Type:	Tanktop Mounted Return Line Filter		
Product Series:	BGT Series		

[Safety Warning](#)

Item Information

BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of handling flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.

LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

- Product Features:
- BGT features pre-filtration by means of a magnet column.
 - Filter heads with multiple ports available.
 - Flow from inside to out.
 - Full flow bypass with low hysteresis.
 - Maximum pressure 10 bar. Maximum flow 2400 l/min.
 - Patented LEIF® elements safeguard filtration quality.



Home CAD Drawings + Files



Products

Support Related Documents



Relat Support

Industries

Services

Solutions

Where to Buy Parker Sales

Where to Buy
Parker Sales Company UK

psc.uk.webform@support.parker.com
+44 (0)1926 317878

+44 (0)1926 317878

+ Company Information

- + Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

