

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Tanktop Mounted R...](#) / BGT17XXBPER484

[Services](#)

# Tanktop Mounted Return Line Filter - BGT Series

[Solutions](#)

Part # BGT17XXBPER484



The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Flow Rate:	0 to 2100 l/min	Product Series:	BGT Series
Division:	Hydraulic and Industrial Process Filtration EMEA	Application:	<ul style="list-style-type: none"> <li>• Mobile cranes</li> <li>• Excavators</li> <li>• Deck cranes</li> <li>• Fire fighting equipment</li> <li>• Hydraulic presses</li> <li>• Waste balers</li> <li>• Industrial power units</li> <li>• Fork lift trucks</li> </ul>
Bypass Valve Pressure Rating:	1.5 bar	Options:	Diffuser type P
Brand:	Parker	Mounting Type:	Tank Mounted
Technology:	Filtration	Seal Material:	Nitrile
Connection Type:	3"SAE	Pressure Rating:	0-34 bar (0-500 psi)
Product Type:	Hydraulic Filter	Housing Material:	Aluminium
Filter Element Type:	No element		
Filter Type:	Tanktop Mounted Return Line Filter		
Micron Rating:	n/a		
Indicator Type:	No indicator, Port plugged R		

[Safety Warning](#)

## Item Information


BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable of handling flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.

LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

### Product Features:

- BGT features pre-filtration by means of a magnet column.
- Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.
- Maximum pressure 10 bar. Maximum flow 2400 l/min.
- Patented LEIF® elements safeguard filtration quality.



 For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor. 

[CAD Drawings + Files](#) 

[Products](#)

[Related Documents](#) 

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)  
[Parker Sales Company UK](#)

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

[+ Company Information](#)

[+ Global Operations](#)

[+ Help & Support](#)

[+ Follow Us :](#)

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---

