=Parker			
<u>Home</u>			
Products			
<u>Support</u>			
Industries			
<u>Services</u>			
Solutions			
Where to Buy			

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / Tanktop Mounted R... / BGT1802QBPXR483

# **Tanktop Mounted Return Line Filter - BGT Series**

## Part #: BGT1802QBPXR483





The BGT Series features pre-filtration by means of a magnet column and a full flow bypass with low hysteresis. Providing maximum flow rates of 2400 l/min at maximum pressure 10 bar.

 $\oplus$ 

View Series Page \Xi Share / Email 📌 Print 🖶

## **Technical Specifications**

Flow Rate:	0 to 900 l/min	Indicator Type:	No indicator, Port plugged R	
Division:	Hydraulic and Industrial Process Filtration EMEA	Options:	Diffuser type T	
Bypass Valve Pressure Rating:	No Bypass		<ul> <li>Mobile cranes</li> <li>Excavators</li> <li>Deck cranes</li> <li>Fire fighting equipment</li> <li>Hydraulic presses</li> <li>Waste balers</li> <li>Industrial power units</li> <li>Fork lift trucks</li> </ul>	
Brand:	Parker	Application:		
Technology:	Filtration			
Connection Type:	3"SAE			
Product Type:	Hydraulic Filter			
Filter Element Type:	02Q Microglass	Mounting Type:	Tank Mounted	
Filter Type:	Tanktop Mounted Return Line Filter	Seal Material:	Nitrile	
Micron Rating:	2 μm	Pressure Rating:	0-34 bar (0-500 psi)	
Product Series:	BGT Series	Housing Material:	Aluminium	
▲ Safety Warning				

## **Item Information**

BGT tanktop mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hyster Thanks to the 'In-to-Out' filter principle, contaminated oil cannot leak back into the system. BGT Filters are available in versions capable flow rates up to 2400 l/min. They can operate with a maximum working pressure of 10 bar.

•) ng

LEIF® elements are available for environment-friendly filtration for versions up to 1500 l/min.

Product Features:

- BGT features pre-filtration by means of a magnet column.
- · Filter heads with multiple ports available.
- Flow from inside to out.
- Full flow bypass with low hysteresis.
- Maximum pressure 10 bar. Maximum flow 2400 l/min.
- Patented LEIF® elements safeguard filtration quality.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

#### **CAD Drawings + Files**

## **Related Documents**



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

+

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

 $\bigcirc$