

<u>Home</u>

Products

Support

Industries oducts / Filters, Collecto... / Replacement Filte... / Liquid Filter Ele... / Fulflo Honeycomb ... / C19-4S

Services Fulfio Honeycomb Ultrafine Wound Filter Cartridges | Designed for critical 0.5 micron filtration applications

Part #: C19-4S



Parker has been a leader in filter media innovation and performance since we first invented the Honeycomb[™] Filter Tube over 65 years ago. Parker has the world's largest manufacturing capacity for wound cartridges, offering superior quality.

View Series Page ☷	View Catalog(s) 🖸
Share / Email 🔿	Print 🖶

Technical Specifications

316 Stainless Steel 19 1/2	Micron Rating: Outside Diameter:	0.5 μm 2 7/16 inch
Glass paper with polyester overlay	Inside Diameter: Specifications	1 inch FDA listed as acceptable for potable and edible liquid
Food and Beverage	Met:	contact according to CFR Title 21
domnick hunter	Flow Rate:	3 GPM per 10 inch
Clarification/Prefiltration/Polishing Cotton	End Cap Configuration:	DOE
Wound	Options: Seal Material:	FDA Grade Cotton Fiber No Gasket
	19 1/2 Glass paper with polyester overlay Food and Beverage domnick hunter Clarification/Prefiltration/Polishing Cotton	19 1/2 Outside Diameter: Glass paper with polyester overlay Inside Diameter: Specifications Specifications Food and Beverage Met: domnick hunter Flow Rate: Clarification/Prefiltration/Polishing End Cap Cotton Configuration: Wound Options:

Item Information

Parker has been a leader in filter media innovation and performance since we first invented the Honeycomb[™] Filter Tube over 65 years ago. Parker has the world's largest manufacturing capacity for wound cartridges, offering superior quality along with technical, engineering and marketing support.

Effective removal ratings at nominal 90% efficiency from 0.5µm to 150µm.

- Features/Benefits
- · A broad range of media provide excellent compatibility with a variety of organic solvents, animal, petroleum and vegetable oils
- Optional core covers and end treatments assure fiber migration control
- Multiple length cartridges minimize change-out time, eliminate spacers and are available to fit competitive filter vessels
- FDA grade polypropylene (DOE only) cartridges certified to ANSI/ NSF61 standard for contact with drinking water components
- · Continuous strand winding geometry provides performance consistency
- One-piece metal extended center core option eliminates the need for cartridge guides in all competitive and Fulflo® multi-cartridge vessels

Related Documents
CAD Drawings + Files
Applications • Filtration of Oxidizing Agents • Petroleum Oil Filtration Support • Photo Filtration • Photo Filtration • Potable Liquid Filtration • Potable Liquid Filtration • Potable Liquid Filtration • Dilute Acid Filtration • Dilute Acid Filtration • Dilute Acid Filtration • Prefilter for Mineral Acids Membranes • Whereasto: Burgets & Solvent Filtration
Parket between the stender is available for polypropylene cores Parket pylene, nylon and polyester materials are FDA listed as acceptable for potable and edible liquid contact according to R T 21 or mgrend cap options available Home 9001:2008 registered company



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS. SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS



<u>Home</u>

Products

Support

Industries

Services

Solutions

Where to Buy