

Clariflow-E-Select Pleated Membrane Filter Cartridge | Hydrophilic PES membrane for aqueous applications

Part #: CS-10720-924-4-E



Clariflow® -E-SELECT pleated membrane filter cartridges are optimized for use in microelectronics applications such as DI water and aqueous-based chemicals for removal of both organic and inorganic particulates.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Brand:	Parker	End Cap Material:	Polypropylene
Seal Material:	Viton	Core Type:	Polypropylene
Industry:	Microelectronics	Hose Reinforcement Material & Structure:	Polypropylene
Function:	Clarification/Prefiltration/Polishing	Flow Rate:	1.9gpm/psid per 10 inch cartridge equivalent for 0.04um
Media:	PES (Polyethersulfone)	End Cap Configuration:	226 O-Ring/Fin
Micron Rating (µm):	0.04	Style:	No Insert
Filter Construction:	Pleated Membrane	Length (inch):	20
Outside Diameter:	2.75 inch		

[Safety Warning](#)

Item Information

CClariflow® -E-SELECT filter cartridges are optimized for use in microelectronics applications such as DI water and aqueous-based chemicals. The unique mirrored-anisotropic PES (Polyethersulfone) filter membrane has exceptionally high flow rates and on-stream lifetime while providing consistent removal of both organic and inorganic particulates. The innovative SELECT pleating provides increased performance over competitive filter cartridges. The filter membrane area is increased by over 50% while flows are 40% higher within the same footprint. The result is one of the longest lasting filter cartridges on the market.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

