

Low Pressure In-Line Duplex Filter - DF2035 Series

Part #: DF20353015NVPHD651



The DF2035 is a series of Light weight, low pressure, high flow capacity duplex filters for gear and diesel engine lube system applications. Suitable for flows up to 800 l/min and pressures up to 8 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Seal Material:	Fluorelastomer	Pressure Rating:	8 bar
Bypass Valve Pressure Rating:	2,0 bar	Flow Rate:	800 L/min
Port Type:	DN65/PN16 ref. Square flange & Blind counter flange	Housing Material:	Aluminium
Options:	With bypass	Operating Temperature:	-20 / +120 °C
Mounting Type:	Inline	Filter Element:	015N Cellulose *
		Indicator Type:	Indicator block plugged
		Flow Capacity (l/min):	800 *

 [Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The DF2035 series is a Light weight, high flow capacity duplex filter for gear and diesel engine lube system applications. Its aluminium housing offers a light weight solution for high capacity filtration. The DF2035 filter has Several filtration media options and high dirt holding capacity: It can hold up to three filter elements per reservoir. Two housing lengths available. Maximum flow rate up to 1800 l/min. Maximum pressure 10 bar. 160 mm square flange connections.

Applications:

- Industrial gear systems
- Diesel engine lubricating systems

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

