

Low Pressure In-Line Duplex Filter - DF2070 Series

Part #: DF20702060WVF1HX1601



The DF2070 is a series of low pressure, high flow duplex filters for heavy fuel oil and lube system applications. Suitable for flows up to 1800 l/min and pressures up to 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Seal Material:	Fluorelastomer	Pressure Rating:	10 bar
Bypass Valve Pressure Rating:	2,0 bar	Flow Rate:	1500 L/min
Port Type:	160 mm Square flange & Blind counter flange	Housing Material:	Steel/Cast iron
Options:	With bypass	Operating Temperature:	-20 / +120 °C
Mounting Type:	Inline	Indicator Type:	Electronic 4 LED, PNP, N.O.
		Flow Capacity (l/min):	1500 *
		Filter Element:	060W Wiremesh

[Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The DF2070 series is a low pressure, high flow duplex filter for use with heavy fuel oil and in lubrication system applications. It has a compact, low-depth duplex construction for vertical mounting.

The DF2070 filter combines high flow and high dirt holding capacity with a low pressure drop.

It offers several element media options for heavy fuel oil and lube systems.

Maximum flow rate up to 1800 l/min. Maximum pressure 10 bar. 160 mm square flange connections.

Applications:

- Diesel engine lubricating systems

- High flow industrial lubricating systems
- High flow heavy fuel oil systems as safety filter

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

