

## Low Pressure In-Line Duplex Filter - DF2110 Series

Part #: DF2110105QVPJD801



The DF2110 duplex filter is a cast iron duplex filter for marine applications. Suitable for flows up to 1200 l/min and pressures up to 30 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

### Technical Specifications

Bypass Valve Pressure Rating:	3.0 bar	Pressure Rating:	30 bar
Micron Rating:	5 µm	Flow Rate:	1000 L/min
Filter Element Type:	05Q Microglass	Housing Material:	Cast iron
Flow Rate:	600 l/min	Operating Temperature:	-20 / +120 °C
Seal Material:	Fluorelastomer	Indicator Type:	Indicator block plugged
Port Type:	DN80/PN25	Options:	With bypass
Mounting Type:	Inline		

[Safety Warning](#)

### Item Information

Items marked with an asterisk \* in the drop-down menus are standard choices.

The DF2110 is a heavy duty performance duplex filter. The elements of the DF2110 have a high dirt holding capacity, yet a low pressure drop. The heavy duty cast iron housing and several element media options mean a multitude of suitable applications. Maximum flow rate up to 1200 l/min and extended housing available for high viscosity oils and longer service intervals. Maximum pressure 30 bar. DN80-PN25 connections.

Applications:

- Marine gear lubricating systems



- Propulsion systems
- Diesel engine lubricating systems
- Heavy fuel oil safety filter

---

## CAD Drawings + Files



---

## Related Documents



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

---

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



