

Low Pressure In-Line Duplex Filter - DF2110 Series

Part #: DF2110220QVT1HD801



The DF2110 duplex filter is a cast iron duplex filter for marine applications. Suitable for flows up to 1200 l/min and pressures up to 30 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|-------------------------------|------------------|----------------------|----------------|
| Bypass Valve Pressure Rating: | 2.0 bar | Filter Element Type: | 20Q Microglass |
| Options: | With bypass | Flow Rate: | 1200 l/min |
| Indicator Type: | Electrical NO/NC | Micron Rating: | 20 µm |

[Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The DF2110 is a heavy duty performance duplex filter. The elements of the DF2110 have a high dirt holding capacity, yet a low pressure drop. The heavy duty cast iron housing and several element media options mean a multitude of suitable applications. Maximum flow rate up to 1200 l/min and extended housing available for high viscosity oils and longer service intervals. Maximum pressure 30 bar. DN80-PN25 connections.

Applications:

- Marine gear lubricating systems
- Propulsion systems
- Diesel engine lubricating systems
- Heavy fuel oil safety filter

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

