

Low Pressure In-Line Duplex Filter - DF2110 Series


Part #: DF2110220QVT1M3HD801



The DF2110 duplex filter is a cast iron duplex filter for marine applications. Suitable for flows up to 1200 l/min and pressures up to 30 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Bypass Valve Pressure Rating:	2.0 bar	Filter Element Type:	20Q Microglass
Options:	With bypass	Flow Rate:	1200 l/min
Indicator Type:	Electrical NO/NC	Micron Rating:	20 µm
 Safety Warning			

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The DF2110 is a heavy duty performance duplex filter. The elements of the DF2110 have a high dirt holding capacity, yet a low pressure drop. The heavy duty cast iron housing and several element media options mean a multitude of suitable applications. Maximum flow rate up to 1200 l/min and extended housing available for high viscosity oils and longer service intervals. Maximum pressure 30 bar. DN80-PN25 connections.

Applications:

- Marine gear lubricating systems
- Propulsion systems
- Diesel engine lubricating systems
- Heavy fuel oil safety filter



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

