

## Medium Pressure In-Line Duplex Filter - DF40 Series

Part #: DF40110QEVT1KR241



The DF40 duplex filter is a cast iron duplex filter for Marine applications.

Suitable for flows up to 200 l/min and pressures up to 40 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

### Technical Specifications

Micron Rating:	10 µm	Mounting Type:	Inline
Flow Rate:	240 l/min	Pressure Rating:	40 bar
Filter Element Type:	10QE Ecoglass	Housing Material:	Cast Iron (GJS)
Connection Type:	1½" SAE-3000M	Operating Temperature:	-20 / +120 °C
Bypass Valve Pressure Rating:	3.5 bar	Indicator Type:	Electrical NO/NC
Seal Material:	Fluorelastomer	Options:	With bypass

[Safety Warning](#)

### Item Information

Items marked with an asterisk \* in the drop-down menus are standard choices.

The DF40 duplex filter gives you extra flexibility in installation because it can be serviced from the top or the bottom.

The durable cast iron housing makes it an especially good fit for engine room applications.

The DF40 with flow up to 200 l/min and pressure up to 40 bar contains Eco elements which help to save the environment and reduce the customer's disposal costs as no metal parts are included.

This filter also disposes of a double indicator port and test connections which can be isolated with shut-off valves for possible assembly and maintenance.

Applications:

- Fuel filter for diesel engines up to 10 MW



- Lubrication filter for gearboxes and propulsion systems
- Medium pressure duplex filter in hydraulic systems
- In-line return duplex filter in hydraulic systems

---

## CAD Drawings + Files



---

## Related Documents



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

---

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



