

Low Pressure In-Line Duplex Filter - DF60 Series

Part #: DF60102QVF3KX602



The DF60 duplex filter is a cast iron duplex filter for Heavy duty lubrication applications. Suitable for flows up to 350 l/min and pressures up to 30 bar.

[View Series Page](#)
[Share / Email](#)
[Print](#)

Technical Specifications

Mounting Type:	Inline	Maximum Flow Rate:	350 L/min
Flow Rate:	0 to 220 l/min	Port Type:	Square flange 60mm
Filter Element:	02Q1 Microglass	Indicator Type:	Electronic 4 LED, PNP, N.C.
Operating Pressure:	Up to 30 bar	Housing Material:	Cast Iron (GSJ)
Bypass Valve Pressure Rating:	No bypass	Options:	No bypass
Operating Temperature:	-20 / +120 °C	Seal Material:	Fluorelastomer

[Safety Warning](#)

Item Information

The DF60 Series is a heavy duty lubrication duplex filter that offers maximum performance especially in those applications using high viscosity lubricating oil.

The large filtration area of the elements of the DF60 contributes minimizing the element pressure drop. A perfect choice for a gearbox lubrication system where duplex filter is needed for continuous operation.

Applications:

- Gearbox lube oil filter
- Turbine lubrication systems
- Medium pressure hydraulic systems

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

