


Low Pressure In-Line Duplex Filter - DFH2060 Series

Part #: DFH20603015NVNHX1601



The DFH2060 is a series of low pressure, high flow duplex filters for diesel engine and industrial lubricating systems. Suitable for flows up to 2200 l/min and pressures up to 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	2200 L/min	Mounting Type:	Inline
Seal Material:	Fluorelastomer	Pressure Rating:	10 bar
Bypass Valve Pressure Rating:	2,0 bar	Housing Material:	Steel/Cast iron
Port Type:	160 mm Square flange & Blind counter flange	Operating Temperature:	-20 / +120 °C
Options:	With bypass	Filter Element:	015N Cellulose *
		Indicator Type:	No indicator block, ports plugged *

Safety Warning

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The DFH2060 series is a low pressure, high flow, high performance, minimum height duplex filter for use in lubrication system applications. It has a Slim welded housing construction with cast iron change over valve section. The DFH2060 filter is for horizontal mounting, making assembly easier in cranked positions. It offers several element media options for high dirt holding capacities and low pressure drops. One reservoir can be closed for service. The DFH2060 has 160 mm square flange connections that come with mounted blind flanges. Maximum flow rate up to 2200 l/min. Maximum pressue 10 bar.

Applications:

- Heavy duty diesel engine lubricating systems
- High flow industrial lubricating systems

CAD Drawings + Files

Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



