

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure Sta...](#) / [EAPF1110QIBPMG081](#)

[Services](#)

[Solutions](#)

# High Pressure Stainless Steel In-line Filter - EAPF iProtect® Series

Part # EAPF1110QIBPMG081



EAPF iProtect® stainless steel in-line filter series is designed to provide high quality filtration of hydraulic systems in marine, oil and gas and process equipment markets covering a flow range up to 120l/min at max 690 bar pressure level.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Flow Rate:	0 to 70 l/min	Options:	Standard
Division:	Hydraulic and Industrial Process Filtration EMEA	Indicator Type:	No indicator
Bypass Valve Pressure Rating:	7.0 bar	Industry:	<ul style="list-style-type: none"> <li>• Oil and Gas</li> <li>• Marine</li> <li>• Process Equipment</li> <li>• Drilling equipment</li> <li>• Lifting equipment</li> <li>• Sub sea systems</li> <li>• Deck equipment</li> <li>• Flushing rigs</li> <li>• Chemical injection</li> </ul>
Brand:	Parker	Application:	
Technology:	Filtration	Indicator Pressure Setting:	No indicator
Connection Type:	G1/2	For Fluid Type:	Hydraulic Oil
Filter Element Type:	10QI Quantumfiber™	Seal Material:	Nitrile
Product Type:	Hydraulic Oil Filter		
Micron Rating:	10 µm		
Filter Type:	High Pressure Inline Filter		
Product Series:	EAPF iProtect® Series		

[Safety Warning](#)

## Item Information

EAPF iProtect® stainless steel filters series has patented element design which guarantees the quality of filtration directly impacting the system reliability.

The iProtect® product applies a re-usable element core which can be combined with a bypass valve, reducing the environmental impact over 50% typically.

The EAPF applies twin seal technology ensuring that external contamination including water cannot ingress the threaded connection between the filter head and bowl. A special hole pattern is applied in the bowl for decompression of the threaded area.

EAPF filter is ATEX certified filter housing and is available with ATEX approved indicators.

Typical Applications



- Deck equipment
- Flushing rigs
- Chemical injection

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

[Home](#)  
**CAD Drawings + Files**



[Products](#)  
**Related Documents**



[Services](#)  
**Where to Buy**



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ [Company Information](#)

+ [Global Operations](#)

+ [Help & Support](#)

+ [Follow Us :](#)

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---