

 \bigcirc

Deck and mobile cranes, Forwarders, Hydraulic presses, Marine steering units, Power packs, Excavators,

Harvesters, Reach stackers, Wheeled loaders, Drilling

equipment, Industrial power units, Wind turbines

Home

Products

Support

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / EPF1105QIBT1MG081

High Pressure Inline Hydraulic Oil Filter - iProtect® EPF Series

WPharet t#BE/PF1105QIBT1MG081





The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

View Series Page

Share / Email

Print

Pr

Technical Specifications

Bypass Valve (bar):

Filter Element: 05QI (Microglass)

Port Connection G1/2

Type: Flow Capacity 0 to 35 (l/min): Indicator 5.0 bar Pressure Setting:

Seal Material: Nitrile Brand: Standard, incl. Bypass Options: Flow Rate: 0 to 35 l/min For Fluid Type: Hydraulic Oil **Bypass Valve**

Materials of Pressure Rating: Housing: Iron/Steel Construction: Hydraulic & Industrial Process Filtration Division EMEA Division:

Specifications Degree of filtration determined by multipass test according Connection Type: to ISO 16889 Met:

Application:

Micron Rating:

Technology:

Product Type:

Indicator Type:

Product Series:

5 µm

Filtration, Hydraulics

Hydraulic Oil Filters

Electrical NO/NC

iProtect® EPF

Agriculture, Construction, Oil and Gas, Marine, Mining, Industry: Product Style: Inline Filter Material Handling

Operating Filter Element 450 bar 05QI (Microglass) Pressure: Type:

▲ Safety Warning

Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high pressure filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters with nonreusable elements.

EPF Series filters serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelopes

and the following pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind turbines, drive efiltration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

High patented design of the filter element allows for integration of the bypass valve and element core as re-usable parts in the filter bowl. This makes the filter secure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 phat (100 psi) or no bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

Support Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, 5, 10, and 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits Industries

Features and Benefits:

Services to damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc.

Solutions no time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life

Whene to duly ter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters

- Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements
- · A "clever" design minimizes the likelihood of installation mistakes
- Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.
- Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- Provides OEM branding (labelling)opportunities
- · High efficiency Quantµmfiber™ glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Related Products









Parker Certified Accumulator Service Centers High Pressure Hydraulic Oil Filter Replacement Elements – iProtect® EPF Series

Hydraulic Reservoir Breather / Air Filter -EAB Series Medium Pressure Inline Hydraulic Oil Filter – iProtect® GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support



Ħ

 \bigcirc

<u>Home</u>

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

Products
Support

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

Industries

<u>Services</u>

Solutions

Where to Buy