

 \bigcirc

Home

Products

Support

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / EPF1110QIBPMG081EX

High Pressure Inline Hydraulic Oil Filter - iProtect® EPF Series

Whart t#BE/PF1110QIBPMG081EX





The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

View Series Page

Share / Email

Print

Pr

Technical Specifications

Bypass Valve 7.0 (bar):

Flow Capacity

0 to 40 (I/min): Port Connection

G1/2 Type:

Filter Element: 10QI (Microglass) Inline Mounting Type: Indicator No indicator

Pressure Setting: Brand: Parker Flow Rate: 0 to 40 I/min

Division: Hydraulic & Industrial Process Filtration Division EMEA

Bypass Valve 7.0 bar Pressure Rating: Connection Type:

Industry:

Material Handling Filter Element

10QI (Microglass) Type:

Agriculture, Construction, Oil and Gas, Marine, Mining,

Product Style: Operating Pressure: Operating Temperature:

Met:

Materials of

Specifications

Application:

Deck and mobile cranes, Forwarders, Hydraulic presses, Marine steering units, Power packs, Excavators, Harvesters, Reach stackers, Wheeled loaders, Drilling

equipment, Industrial power units, Wind turbines

Micron Rating: 10 µm Filtration, Hydraulics Technology:

Plugged with steel plug Indicator Type: Product Type: Hydraulic Oil Filters **Product Series:** iProtect® EPF Seal Material: Nitrile Options: For Fluid Type: Hydraulic Oil

Housing: Iron/Steel Construction:

> Degree of filtration determined by multipass test according to ISO 16889

Inline Filter 450 bar, 6500 psi

-40 to +100 °C

▲ Safety Warning

Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high pressure filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters with nonreusable elements.

serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelopes igue pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind the bird systems, prior line filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

Home
The patiented design of the filter element allows for integration of the bypass valve and element core as re-usable parts in the filter bowl. This practice the filter secure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 bar (100 psi) or no bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

Support

The EPF Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, INCLESSED 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits

Services and Benefits:

- Prevents damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc. Solutions
- Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life Where to Buy
- Compact filter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters.
- Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements
- · A "clever" design minimizes the likelihood of installation mistakes
- Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.
- · Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- Provides OEM branding (labelling)opportunities
- High efficiency Quantumfiber™ glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Related Products









Parker Certified Accumulator Service High Pressure Hydraulic Oil Filter Replacement Elements – iProtect® EPF Series

Hydraulic Reservoir Breather / Air Filter -EAB Series Medium Pressure Inline Hydraulic Oil Filter – iProtect® GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations

	Ä	\bigcirc
Hornellow Us:		
<u>Products</u>		
Cunnart	© PARKER HANNIFIN CORP 2023	
Support	ENGINEERING YOUR SUCCESS.	
<u>Industries</u>	SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS	
Services		
Solutions		
Where to Buy		