

Home

Products

Support / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / EPF1110QIBT1MG081

High Pressure Inline Hydraulic Oil Filter - iProtect® EPF Series

<u>Services</u>

sBarit#: EPF1110QIBT1MG081





The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

View Series Page

Share / Email

Print

Pr

Technical Specifications

Bypass Valve (bar): 7.0

Flow Capacity 0 to 40

(l/min):

Port Connection Type: G1/2

Filter Element: 10QI (Microglass)

Indicator
Pressure Setting:
5.0 bar

Brand: Parker
Flow Rate: 0 to 40 l/min
Bypass Valve

Pressure Rating: 7.0 bar

Division: Hydraulic & Industrial Process Filtration Division EMEA

Connection Type:

Industry: Agriculture, Construction, Oil and Gas, Marine, Mining, Material Handling

Filter Element
Type: 10QI (Microglass)

▲ Safety Warning

Deck and mobile cranes, Forwarders, Hydraulic presses,

Marine steering units, Power packs, Excavators,

Harvesters, Packs stackers, Wheeled loaders, Prilling

Harvesters, Reach stackers, Wheeled loaders, Drilling equipment, Industrial power units, Wind turbines

Micron Rating: 10 μm

Technology: Filtration, Hydraulics
Product Type: Hydraulic Oil Filters
Indicator Type: Electrical NO/NC
Product Series: iProtect® EPF
Seal Material: Nitrile

Options: Standard, incl. Bypass
For Fluid Type: Hydraulic Oil

Materials of Construction: Housing: Iron/Steel

Specifications Degree of filtration determined by multipass test according Met: to ISO 16889.

Product Style: Inline Filter
Operating 450 ber

Pressure: 450 bar

Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high pressure filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters with non-reusable elements.

EPF Series filters serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelopes and excellent fatigue pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind turbines, drive systems, pilot line filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

The state of the filter element allows for integration of the bypass valve and element core as re-usable parts in the filter bowl. This cure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

The EPF Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, Prof. at 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits

Streamers and Benefits:

- $\, \bullet \,$ Prevents damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc. $\underline{Industries}$
- Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life Services
- Compact filter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters Solutions
- Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable where to sure.
- · A "clever" design minimizes the likelihood of installation mistakes
- Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.
- · Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- · Provides OEM branding (labelling)opportunities
- High efficiency Quantµmfiber™ glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Related Products









Parker Certified Accumulator Service Centers

High Pressure Hydraulic Oil Filter Replacement Elements – iProtect® EPF Series

Hydraulic Reservoir Breather / Air Filter -EAB Series

Medium Pressure Inline Hydraulic Oil Filter – iProtect® GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us:



© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

Home SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

Products

Support

<u>Industries</u>

<u>Services</u>

Solutions

Where to Buy