

<u>Home</u>

Products

Support

H

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / EPF2105QIBT1MH121

<u>Services</u> High Pressure Inline Hydraulic Oil Filter – iProtect® EPF Series

Whatet#BEPF2105QIBT1MH121



The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

View Series Page 😑 Share / Email 📌 Print 🖨

Technical Specifications

Port Connection 3/4" SAE-6000M equipment, Industrial por	ers, Wheeled loaders, Drilling ower units. Wind turbines
l ype: Micron Rating: 5 μm Filter Element: 05QI (Microglass) Technology: Filtration, Hydraulics	
Flow Capacity (I/min): 0 to 80 Product Type: Hydraulic Oil Filters Indicator Type: Electrical NO/NC	
Pressure Setting: 5.0 bar Seal Material: Nitrile Prand: Parker Product Series: iProtect® EPF	
Flow Rate: 0 to 80 I/min For Fluid Type: Hydraulic Oil Options: Standard incl. Bypass	
Bypass Valve 7.0 bar Materials of Pressure Rating: 7.0 bar Materials of Division: Hydraulic & Industrial Process Filtration Division EMEA Construction:	
Connection Type: 3/4" SAE-6000M Specifications Degree of filtration determined by the second	rmined by multipass test according
Industry: Agriculture, Construction, Oil and Gas, Marine, Mining, Material Handling Product Style: Inline Filter Filter Element Operating 450 bar	
Type: 05QI (Microglass) Pressure: 450 bar	

Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high pressure filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters with non-reusable elements.

EPF Series filters serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelopes



tigue pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind turbines, drive a filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve application 层 🖄 🖵 🗂 🖓 🗛 Intration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve application 😹

Hone patented design of the filter element allows for integration of the bypass valve and element core as re-usable parts in the filter bowl. This makes the filter secure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 phan (100 psi) or no bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

Support Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, 5, 10, and 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits Industries

Features and Benefits:

Sepvices ts damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc.

Solutions no between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life

Whene the Aulter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters

• Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements

· A "clever" design minimizes the likelihood of installation mistakes

· Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.

- · Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- Provides OEM branding (labelling)opportunities
- High efficiency Quantµmfiber[™] glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents

Related Products

Parker Certified Accumulator Service Centers

High Pressure Hydraulic Oil Filter Replacement Elements - iProtect® EPF Series

Hydraulic Reservoir Breather / Air Filter -EAB Series

Medium Pressure Inline Hydraulic Oil Filter - iProtect® **GMF** Series



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support



<u>Home</u>

Products

Support

Industries

Services

Solutions

Where to Buy

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS