

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure Inl...](#) / [EPF2110QIHBT1MX122](#)

[Services](#)

[Solutions](#)

High Pressure Inline Hydraulic Oil Filter – iProtect® EPF Series

Part # EPF2110QIHBT1MX122



The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Bypass Valve (bar):	No Bypass with 5.0 bar indicator	Application:	Deck and mobile cranes, Forwarders, Hydraulic presses, Marine steering units, Power packs, Excavators, Harvesters, Reach stackers, Wheeled loaders, Drilling equipment, Industrial power units, Wind turbines
Filter Element:	10QIH (High Strenght Microglass)	Micron Rating:	10 µm
Port Connection Type:	Manifold Ø22,23 mm (7/8")	Technology:	Filtration, Hydraulics
Flow Capacity (l/min):	0 to 80	Indicator Type:	Electrical NO/NC
Mounting Type:	Manifold side mounting	Product Type:	Hydraulic Oil Filters
Indicator		Seal Material:	Nitrile
Pressure Setting:	5.0 bar	Product Series:	iProtect® EPF
Flow Rate:	0 to 80 l/min	For Fluid Type:	Hydraulic Oil
Brand:	Parker	Options:	No Bypass
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Materials of Construction:	Housing: Iron/Steel
Bypass Valve	No Bypass with 5.0 bar indicator	Specifications Met:	Degree of filtration determined by multipass test according to ISO 16889.
Pressure Rating:		Product Style:	Inline Filter
Connection Type:	Manifold Ø22,23 mm (7/8")	Operating Pressure:	450 bar, 6500 psi
Industry:	Agriculture, Construction, Oil and Gas, Marine, Mining, Material Handling	Operating Temperature:	-40 to +100 °C
Filter Element Type:	10QIH (High Strength Microglass)		

[Safety Warning](#)

Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters reusable elements.



EPF Series filters serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelopes and unique pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind turbines drive systems, pilot line filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

Home

Products

Support

The EPF Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, 5, 10, and 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits

Services

Features and Benefits:

- Prevents damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc.

Solutions

- Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life

Where to Buy

- Compact filter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters

- Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements

- A "clever" design minimizes the likelihood of installation mistakes

- Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.

- Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.

- Provides OEM branding (labelling) opportunities

- High efficiency Quantumfiber™ glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Related Products

Parker Certified
Accumulator Service
Centers

High Pressure
Hydraulic Oil Filter
Replacement
Elements – iProtect®
EPF Series

Hydraulic Reservoir
Breather / Air Filter -
EAB Series

Medium Pressure
Inline Hydraulic Oil
Filter – iProtect®
GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations





[Home](#) Follow Us :

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

© PARKER HANNIFIN CORP 2023

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

