

# High Pressure Inline Hydraulic Oil Filter – iProtect® EPF Series

Part # EPF2110QIRBPKG12RFV



The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

<p><b>Bypass Valve (bar):</b> 3.5</p> <p><b>Filter Element:</b> 10QIR (Microglass - Reverse Flow)</p> <p><b>Flow Capacity (l/min):</b> 0 to 100</p> <p><b>Port Connection Type:</b> G3/4</p> <p><b>Indicator Pressure Setting:</b> No indicator</p> <p><b>Flow Rate:</b> 0 to 100 l/min</p> <p><b>Brand:</b> Parker</p> <p><b>Division:</b> Hydraulic &amp; Industrial Process Filtration Division EMEA</p> <p><b>Bypass Valve Pressure Rating:</b> 3.5 bar</p> <p><b>Connection Type:</b> G%</p> <p><b>Industry:</b> Agriculture, Construction, Oil and Gas, Marine, Mining, Material Handling</p> <p><b>Filter Element Type:</b> 10QIR (Microglass - Reverse Flow)</p>	<p><b>Application:</b> Deck and mobile cranes, Forwarders, Hydraulic presses, Marine steering units, Power packs, Excavators, Harvesters, Reach stackers, Wheeled loaders, Drilling equipment, Industrial power units, Wind turbines</p> <p><b>Micron Rating:</b> 10 µm</p> <p><b>Technology:</b> Filtration, Hydraulics</p> <p><b>Indicator Type:</b> Plugged with steel plug</p> <p><b>Product Type:</b> Hydraulic Oil Filters</p> <p><b>Seal Material:</b> Nitrile</p> <p><b>Product Series:</b> iProtect® EPF</p> <p><b>Options:</b> Reverse flow valve incl. Bypass</p> <p><b>For Fluid Type:</b> Hydraulic Oil</p> <p><b>Materials of Construction:</b> Housing: Iron/Steel</p> <p><b>Specifications Met:</b> Degree of filtration determined by multipass test according to ISO 16889.</p> <p><b>Product Style:</b> Inline Filter</p> <p><b>Operating Pressure:</b> 450 bar</p>
--	--

[Safety Warning](#)

## Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high pressure filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters with non-reusable elements.

EPF Series filters serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelope is required.



and high fatigue pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind turbines, drive shafts, filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

The patented design of the filter element allows for integration of the bypass valve and element core as re-usable parts in the filter bowl. This makes the filter secure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 bar (100 psi) or no bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

The EPF Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, 5, 10, and 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits

#### Industries

#### Features and Benefits:

Prevents damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc.

Reduces time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life

Where a filter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters

- Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements
- A "clever" design minimizes the likelihood of installation mistakes
- Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.
- Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- Provides OEM branding (labelling) opportunities
- High efficiency Quantumfiber™ glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

## CAD Drawings + Files



## Related Documents



## Related Products

Parker Certified  
Accumulator Service  
Centers

High Pressure  
Hydraulic Oil Filter  
Replacement  
Elements – iProtect®  
EPF Series

Hydraulic Reservoir  
Breather / Air Filter -  
EAB Series

Medium Pressure  
Inline Hydraulic Oil  
Filter – iProtect®  
GMF Series



Parker Sales Company UK

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

