

<u>Home</u>

Products

Support

H

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / EPF3102QIBM3MG161

Services High Solutions Pressure Inline Hydraulic Oil Filter – iProtect® EPF Series

Whatett#BEvPF3102QIBM3MG161



The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

Ð

View Series Page 😑 Share / Email 📌 Print 🖨

Technical Specifications

Bypass Valve (bar): Port Connection	7.0 G1	Application:	Deck and mobile cranes, Forwarders, Hydraulic presses, Marine steering units, Power packs, Excavators, Harvesters, Reach stackers, Wheeled loaders, Drilling equipment, Industrial power units, Wind turbines
Туре:		Micron Rating:	2 µm
Flow Capacity (I/min):	0 to 140	Technology:	Filtration, Hydraulics
Filter Element:	02QI (Microglass)	Indicator Type:	Visual
Indicator		Product Type:	Hydraulic Oil Filters
Pressure Setting:	5.0 bar	Product Series:	iProtect® EPF
Brand:	Parker	Seal Material:	Nitrile
		For Fluid Type:	Hydraulic Oil
Flow Rate:	0 to 140 l/min	Options:	Standard, incl. Bypass
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Materials of	
Bypass Valve Pressure Rating:	7.0 bar	Construction:	Housing: Iron/Steel
Connection Type:	G1	Specifications	Degree of filtration determined by multipass test according
Inductor	Agriculture, Construction, Oil and Gas, Marine, Mining,	Met:	to ISO 16889.
Industry:	Material Handling	Product Style:	Inline Filter
Filter Element Type:	02QI (Microglass)	Operating Pressure:	450 bar
A Safety Warning			

Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high pressure filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters w^{ist} on-reusable elements.

EPF Series filters serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact enve.



tigue pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind turbines, drive e filtration systems. servo controls. industrial working hydraulics, control systems, and reverse flow valve application s201 Core filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

Home atented design of the filter element allows for integration of the bypass valve and element core as re-usable parts in the filter bowl. This makes the filter secure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 phan (100 psi) or no bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

Support Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, 5, 10, and 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits Industries

Features and Benefits:

Services ts damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc.

Solutions no between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life

Whene the Aulter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters

• Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements

· A "clever" design minimizes the likelihood of installation mistakes

• Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.

- · Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- Provides OEM branding (labelling)opportunities
- High efficiency Quantµmfiber[™] glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents

Related Products



Centers

Parker Certified Accumulator Service



High Pressure Hydraulic Oil Filter Replacement Elements - iProtect® EPF Series



Hydraulic Reservoir

Breather / Air Filter -

EAB Series



Medium Pressure Inline Hydraulic Oil Filter - iProtect® **GMF** Series



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support

-		
	ы	

<u>Home</u>

Products

Support

Industries

Services

Solutions

Where to Buy

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS