=Parker			
<u>Home</u>			
Products			
Support			
Industries			
<u>Services</u>			
Solutions			
<u>Where to Buy</u>			

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / EPF3105QIBM3MG161

High Pressure Inline Hydraulic Oil Filter – iProtect® EPF Series

Part #: EPF3105QIBM3MG161

H



The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

View Series Page 😑 Share / Email 📌 Print 🖨

Technical Specifications

Bypass Valve (bar): Port Connection	7.0 G1	Application:	Deck and mobile cranes, Forwarders, Hydraulic presses, Marine steering units, Power packs, Excavators, Harvesters, Reach stackers, Wheeled loaders, Drilling equipment, Industrial power units, Wind turbines	
Туре:	61	Micron Rating:	5 μm	
Filter Element:	05QI (Microglass)	Technology:	Filtration, Hydraulics	
Flow Capacity (I/min):	0 to 170	Indicator Type:	Visual	
Indicator	5.0 bar	Product Type: Product Series:	Hydraulic Oil Filters iProtect® EPF	
Pressure Setting: Brand:	Parker	Seal Material: Options:	Nitrile Standard, incl. Bypass	
Flow Rate:	0 to 170 l/min	For Fluid Type:	Hydraulic Oil	
Bypass Valve Pressure Rating:	7.0 bar	Materials of Construction: Specifications	Housing: Iron/Steel	
Division:	Hydraulic & Industrial Process Filtration Division EMEA		Degree of filtration determined by multipass test according to ISO 16889.	
Connection Type:	G1	Met:		
Industry:	Agriculture, Construction, Oil and Gas, Marine, Mining, Material Handling	Product Style:	Inline Filter	
Filter Element Type:	05QI (Microglass)	Operating Pressure:	450 bar	
\Lambda Safety Warning				

Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high pressure filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters with non-reusable elements.

EPF Series filters serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelopes and excellent fatigue pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind turbines, drive systems, pilot line filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

The patented design of the filter element allows for integration of the bypass valve and element core as re-usable parts in the filter bowl. This makes the filter secure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 bar (100 psi) or no bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

The EPF Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, 5, 10, and 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits

Features and Benefits:

· Prevents damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc.

- · Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life
- · Compact filter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters

• Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements

· A "clever" design minimizes the likelihood of installation mistakes

• Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.

- · Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- · Provides OEM branding (labelling)opportunities
- High efficiency Quantµmfiber™ glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents Related Products



Parker Certified Accumulator Service Centers



High Pressure Hydraulic Oil Filter Replacement Elements – iProtect® EPF Series



Hydraulic Reservoir Breather / Air Filter -EAB Series



Medium Pressure Inline Hydraulic Oil Filter – iProtect® GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com

<u>+44 (0)1926 317878</u>

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.