





Home

Products

Support

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / EPF4210QIRVM3KG24RFV

High Pressure Inline Hydraulic Oil Filter - iProtect® EPF Series

Whart t#BEPF4210QIRVM3KG24RFV





The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

View Series Page

Share / Email

Print

Pr

Technical Specifications

Flow Capacity 0 to 500 (l/min):

Bypass Valve 3.5

(bar):

Filter Element: 10QIR (Microglass - Reverse Flow)

Port Connection G1-1/2 Type: Mounting Type: Inline Indicator 2.5 bar

Pressure Setting: Flow Rate: 0 to 500 l/min Brand: Parker

Division: Hydraulic & Industrial Process Filtration Division EMEA

Bypass Valve 3.5 bar Pressure Rating: Connection Type:

Agriculture, Construction, Oil and Gas, Marine, Mining, Industry:

Material Handling

Filter Element 10QIR (Microglass - Reverse Flow) Type:

Deck and mobile cranes, Forwarders, Hydraulic presses, Application:

Marine steering units, Power packs, Excavators, Harvesters, Reach stackers, Wheeled loaders, Drilling equipment, Industrial power units, Wind turbines

Micron Rating: 10 µm

Filtration, Hydraulics Technology:

Indicator Type: Visual

Product Type: Hydraulic Oil Filters Seal Material: Fluorelastomer **Product Series:** iProtect® EPF For Fluid Type: Hydraulic Oil

Options: Reverse flow valve incl. Bypass

Materials of Housing: Iron/Steel Construction:

Specifications Degree of filtration determined by multipass test according to ISO 16889. Met:

Product Style: Inline Filter Operating

450 bar, 6500 psi Pressure:

Operating -20 to +120 °C Temperature:

▲ Safety Warning

Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element reinside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters reusable elements.

serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelopes igue pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind the bird systems, pilot line filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

Home
The patented design of the filter element allows for integration of the bypass valve and element core as re-usable parts in the filter bowl. This product the filter secure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 bar (100 psi) or no bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

The EPF Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, Industries 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits

Services and Benefits:

- Prevents damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc. Solutions
- Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life Where to Buy
- Compact filter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters.
- Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements
- · A "clever" design minimizes the likelihood of installation mistakes
- Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.
- · Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- Provides OEM branding (labelling)opportunities
- High efficiency Quantumfiber™ glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents

+

Related Products

Parker Certified Accumulator Service Centers High Pressure Hydraulic Oil Filter Replacement Elements – iProtect® EPF Series

Hydraulic Reservoir Breather / Air Filter -EAB Series Medium Pressure Inline Hydraulic Oil Filter – iProtect® GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information

+ Global Operations



i—⊃arker ^t		Ħ	<u>>></u>
Homelow Us:			
<u>Products</u>			
Support	© PARKER HANNIFIN CORP 2023		
	ENGINEERING YOUR SUCCESS.		
<u>Industries</u>	SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS		
<u>Services</u>			
Solutions			
Where to Buy			