

 $\bigcirc$ 

Home

**Products** 

Support

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / EPF5105QIBPMH241

## High Pressure Inline Hydraulic Oil Filter - iProtect® EPF Series

WPharet t#BEDPF5105QIBPMH241





The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

View Series Page 

Share / Email 

Print 

Pr

## **Technical Specifications**

Bypass Valve 7.0 (bar):

Flow Capacity

0 to 500 (I/min):

Filter Element: 05QI (Microglass)

Port Connection 1-1/2" SAE-6000M

Type:

Mounting Type: Inline Indicator No indicator Pressure Setting: 0 to 500 l/min

Flow Rate: Brand: Parker **Bypass Valve** 7.0 bar Construction:

Hydraulic & Industrial Process Filtration Division EMEA Division:

Met: Connection Type:

Agriculture, Construction, Oil and Gas, Marine, Mining,

Industry: Material Handling

Filter Element

05QI (Microglass) Type:

▲ Safety Warning

Pressure Rating:

Deck and mobile cranes, Forwarders, Hydraulic presses, Marine steering units, Power packs, Excavators, Application:

Harvesters, Reach stackers, Wheeled loaders, Drilling equipment, Industrial power units, Wind turbines

Micron Rating: 5 µm

Filtration, Hydraulics Technology: Hydraulic Oil Filters Product Type: Indicator Type: Plugged with steel plug

Nitrile Seal Material: **Product Series:** iProtect® EPF Options: Standard, incl. Bypass

For Fluid Type: Hydraulic Oil Materials of Housing: Iron/Steel

Specifications Degree of filtration determined by multipass test according to ISO 16889

Product Style: Inline Filter Operating 450 bar, 6500 psi

Pressure: Operating -40 to +100 °C

Temperature:

## Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high pressure filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters with nonreusable elements.

serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelopes igue pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind the bird systems, prior line filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

Home
The patiented design of the filter element allows for integration of the bypass valve and element core as re-usable parts in the filter bowl. This practically filter secure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 bar (100 psi) or no bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

Support

The EPF Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, Industries 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits

## Services and Benefits:

- Prevents damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc. Solutions
- Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life <a href="https://www.when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com/when.edu.networder.com
- Compact filter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters.
- Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements
- · A "clever" design minimizes the likelihood of installation mistakes
- Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.
- · Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- Provides OEM branding (labelling)opportunities
- High efficiency Quantumfiber™ glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files	+
Related Documents	+



**Parker Sales Company UK** 

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company	Information
-----------	-------------

- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS





<u>Home</u>

**Products** 

<u>Support</u>

**Industries** 

<u>Services</u>

**Solutions** 

Where to Buy