

Home

Products

Support

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / EPF5110QIRBT1KH24RFV Industries

Services | Pressure Inline Hydraulic Oil Filter - iProtect® EPF Series

Part # EPF5110QIRBT1KH24RFV





The Parker EPF Series is a highly compact, eco-friendly inline hydraulic oil filter that features a re-usable element core. Capable of flows up to 700 L/min (185 GPM). Maximum allowable operating pressure 450 bar (6,500 psi).

View Series Page **:** Share / Email **→** Print **-**

Technical Specifications

Bypass Valve (bar):

Filter Element: 10QIR (Microglass - Reverse Flow)

Port Connection 1-1/2" SAE-6000M

Type:

Flow Capacity 0 to 550 (I/min):

Indicator 2.5 bar Pressure Setting: Brand: Flow Rate: 0 to 550 I/min

Division: Hydraulic & Industrial Process Filtration Division EMEA Bypass Valve

3.5 bar Pressure Rating: Connection Type: 11/2" SAE-6000M

Agriculture, Construction, Oil and Gas, Marine, Mining, Industry:

Material Handling

Filter Element 10QIR (Microglass - Reverse Flow) Type:

∧ Safety Warning

Deck and mobile cranes, Forwarders, Hydraulic presses, Marine steering units, Power packs, Excavators, Application: Harvesters, Reach stackers, Wheeled loaders, Drilling

equipment, Industrial power units, Wind turbines

Micron Rating: 10 µm

Technology: Filtration, Hydraulics Product Type: Hydraulic Oil Filters Indicator Type: Electrical NO/NC Nitrile

Seal Material: **Product Series:** iProtect® EPF

Reverse flow valve incl. Bypass Options:

Hydraulic Oil

For Fluid Type: Materials of

Housing: Iron/Steel Construction:

Specifications Degree of filtration determined by multipass test according

to ISO 16889 Product Style: Inline Filter

Operating 450 bar Pressure:

Item Information

The Parker EPF Series is a high pressure, inline hydraulic oil filter that provides high-efficiency filtration for equipment in demanding environments, including mining, construction, marine, drilling, and agricultural applications. A unique feature of the EPF Series is that the filter element remains inside the filter bowl when performing a change-out. This can save over 500 mm of space envelope in comparison with traditional high pressure filters on the market. The filter element core is also reusable, which reduces waste by up to 50% when compared to conventional filters with nonreusable elements.

EPF Series filters serve as a highly economical filtration solution in high pressure range applications (up to 450 bar), where compact envelopes and excellent fatigue pressure ratings are critical. Specific examples include (but are not limited to) mobile working hydraulics, wind turbines, drive filtration systems, servo controls, industrial working hydraulics, control systems, and reverse flow valve applications.

makes the filter secure and eliminates the risk of forgetting to re-install reusable parts during maintenance. Bypass settings are available up to 7 bar (100 psi) or no bypass versions when using patented, high strength filter elements. The principle is based on differential pressure measurement across the filter element.

The EPF Series is designed for use with EPF Series Replacement Elements and is available with various port connection types, filtration media (2, SUPPORT 20 micron), indicators, and flow capacities (up to 700 L/min) to meet the unique requirements of customers' hydraulic circuits

Inclustries and Benefits:

- Prevents damaging of hydraulic circuits or machinery done by dirt, sand, dust, metal, etc.
- Services
- Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life <u>Solutions</u>
- · Compact filter design can save over 500 mm of space envelope when compared to traditional inline hydraulic filters

Where to Buy

- Reusable element core with patented filtration technology reduces waste by up to 50% when compared to conventional filters with non-reusable elements
- · A "clever" design minimizes the likelihood of installation mistakes
- Can be equipped with an optional reverse flow. This valve assembly is integrated in the element end cap and isolates the filter medium during reverse flow conditions.
- Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- · Provides OEM branding (labelling)opportunities
- High efficiency Quantµmfiber™ glass media increases particle capture and dirt holding capacity.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents

+

Related Products

Parker Certified Accumulator Service Centers High Pressure Hydraulic Oil Filter Replacement Elements – iProtect® EPF Series

Hydraulic Reservoir Breather / Air Filter -EAB Series Medium Pressure Inline Hydraulic Oil Filter – iProtect® GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support

:—Parker	
<u>Home</u>	© PARKER HANNIFIN CORP 2023
<u>Products</u>	ENGINEERING YOUR SUCCESS.
Support	SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS
<u>Industries</u>	
<u>Services</u>	
Solutions	

Where to Buy