

## Tank Top Mounted Return Line Filter - ETF Series

Part #: ETF110QBG2FG161



The ETF series is a light weight and economic tank top mounted return line filter. Providing maximum flow rate of 175 l/min and maximum pressure 6 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

### Technical Specifications

|                               |  |                        |   |
|-------------------------------|--|------------------------|---|
| Flow Rate:                    | 0 to 70 l/min                                    | Filter Type:           | Tanktop Mounted Return Line Filter  |
| Filter Element Type:          | 10Q Microglass                                   | Pressure Rating:       | 6 bar, Maximum: 1.6 bar (23 psi)  |
| Division:                     | Hydraulic and Industrial Process Filtration EMEA | Product Series:        | ETF series  |
| Brand:                        | Parker   | Application:           | <ul style="list-style-type: none"><li>• Lorry Mounted Cranes</li><li>• Agricultural Equipment</li><li>• Container Hhook Loaders</li></ul> |
| Bypass Valve Pressure Rating: | 1,6 bar, 1.6 bar (23 psi)                        | Housing Material:      | Glass reinforced co-polymer, Glass Reinforced Co-polymer  |
| Micron Rating:                | 10 µm  | Mounting Type:         | Tank Mounted  |
| Technology:                   | Filtration                                       | Operating Temperature: | -20 / +80 °C, -20 / +80°C (-4 / +176°F)   |
| Indicator Type:               | Visual   | Connection Size:       | G1  |
| Product Type:                 | Hydraulic Filter                                 | Seal Material:         | Nitrile   |
| Options:                      | No diffuser                                      |                        |   |

[Safety Warning](#)

### Item Information

The Parker Filtration ETF Series is an economic tank top mounted return line filter that has been used and proven in many hydraulic filtration applications.

It utilizes a re-inforced co-polymer head equipped with 2 return ports and quick-release cover.

For use in hydraulic systems with nominal flows up to 175 l/min and a maximum pressure of 6 bar.

Product Features:

- A re-inforced co-polymer head equipped with 2 return ports.
- Quick-release cover design.
- Flow from inside to out.
- Maximum pressure 6 bar. Maximum flow 175 l/min.
- An economic return line filter for hydraulic systems.

Typical Applications:

- Lorry mounted cranes
- Agricultural equipment
- Container hook loaders

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

---

## CAD Drawings + Files



---

## Related Documents



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

---

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

