
≡ —Parker		
<u>Home</u>		
Products		
<u>Support</u>		
Industries		
<u>Services</u>		
Solutions		
Where to Buy		

Home / Products / Regulators, Monit... / Monitoring / Fuel Drip Bunker ... / FG-K1-125-KW

Fuel Drip Bunker Samplers

Part #: FG-K1-125-KW





Manufactured from stainless steel.

View Series Page 🚍 Share / Email 📌 Print 🖶

Technical Specifications

Brand: Kittiwake Division: Hydraulic & Industrial Process Filtration Division EMEA Industry: Marine Pipe Outside Diameter: Technology: Product Type: Product Style: For Fluid Type: **Operating Pressure:** Operating Temperature: Minimum Fluid Temperature:

125 mm Filtration, Hydraulics Sampling System Sample Capture Device Lube Oil Fuel 40 bar, 580 psi -50 to 75 °C, -58 to 167 °F -50 °C, -58 °F

Maximum Fluid Temperature: Flow Rate: Sensing Method: Height: Width: Outside Diameter: Port Size: Port Type: Materials of Construction: Body Material: Seal Material: Specifications Met: 75 °C, 167 °F

n/a n/a 608 mm 31.5 mm 188 mm 5 inch

Pipe bore

Stainless Steel

Stainless Steel

Nitrile Rubber MARPOL regulations, IMO, ISO TR 13729 and Singapore Bunkering Procedure, ASTM D 4057, BS 3195, ISO 3170

Safety Warning

Item Information

May 19th 2005 was the implementation date for IMO MARPOL Annex VI legislation, and ships the world over are using Parker Kittiwake equipment to adhere to these regulations. Parker Kittiwake supplies a full range of in-line bunker samplers and bunker sampling access complete range of sample bottles and consumables, plus a Germanischer LLoyd certified Bunker Sample Storage System.



Parker Kittiwake has a wide selection of bunker samplers and equipment ex-stock, ready for immediate delivery. There could not be a better time to ensure that you are IMO MARPOL compliant. Contact your local Parker representative for further details and to place your order.

Bunker samplers are designed to provide a representative sample of the entire fuel delivery. Manufactured from stainless steel, all products comply with ISO 3170, BS 3195, ASTM D 4057 and ISO TR 13729 standards, as well as the Singapore Bunkering Procedure.

Features and Benefits

- · Lightweight and very easy to install
- Joint rings included
- All sizes available ex-stock UK
- · Comprehensive accessories and consumables

CAD Drawings + Files

Related Documents

+ +



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

 \bigcirc