



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

[Home](#) / [Products](#) / [Regulators, Monit...](#) / [Monitoring](#) / [Fuel Drip Bunker ...](#) / [FG-K1-129-KW](#)

Fuel Drip Bunker Samplers

Part #: FG-K1-129-KW



Parker bunker samplers are designed to provide a representative sample of the entire fuel delivery. Manufactured from stainless steel.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Brand:	Kittiwake	Maximum Fluid Temperature:	75 °C, 167 °F
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Flow Rate:	n/a
Industry:	Marine	Sensing Method:	n/a
Technology:	Filtration, Hydraulics	Height:	727 mm
Product Type:	Sampling System	Width:	31.5 mm
Product Style:	Sample Capture Device	Outside Diameter:	307 mm
Pipe Outside Diameter:	225 mm	Port Size:	9 inch
For Fluid Type:	Lube Oil Fuel	Port Type:	Pipe bore
Operating Pressure:	40 bar, 580 psi	Materials of Construction:	Stainless Steel
Operating Temperature:	-50 to 75 °C, -58 to 167 °F	Body Material:	Stainless Steel
Minimum Fluid Temperature:	-50 °C, -58 °F	Seal Material:	Nitrile Rubber
		Specifications Met:	MARPOL regulations, IMO, ISO TR 13729 and Singapore Bunkering Procedure, ASTM D 4057, BS 3195, ISO 3170

[Safety Warning](#)

Item Information

May 19th 2005 was the implementation date for IMO MARPOL Annex VI legislation, and ships the world over are using Parker Kittiwake equipment to adhere to these regulations. Parker Kittiwake supplies a full range of in-line bunker samplers and bunker sampling access complete range of sample bottles and consumables, plus a Germanischer Lloyd certified Bunker Sample Storage System.



Parker Kittiwake has a wide selection of bunker samplers and equipment ex-stock, ready for immediate delivery. There could not be a better time to ensure that you are IMO MARPOL compliant. Contact your local Parker representative for further details and to place your order.

Bunker samplers are designed to provide a representative sample of the entire fuel delivery. Manufactured from stainless steel, all products comply with ISO 3170, BS 3195, ASTM D 4057 and ISO TR 13729 standards, as well as the Singapore Bunkering Procedure.

Features and Benefits

- Lightweight and very easy to install
- Joint rings included
- All sizes available ex-stock UK
- Comprehensive accessories and consumables

CAD Drawings + Files +

Related Documents +



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



